

DesignLights Consortium



Classification	Standard
Primary Use	Direct Linear Ambient Luminaires
Reported Input Wattage	72 W
Reported Light Output	9792 lm
Reported CCT	5000 K
Reported CRI (Ra)	80
Product ID	S-PQ1RGU
DLC Family Code	BBBGCN
Listing Status	Listed
Date Qualified	2022-08-26

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-PQ1RGU
Manufacturer	Halco Lighting Technologies
Brand	ProLED
Model Number	LS8/72U50/[Blank,EM,MS]
Parent	No
Classification	Standard
DLC Family Code	BBBGCN
Length	8.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Linear Ambient
Primary Use Designation	Direct Linear Ambient Luminaires

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Multifunction Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	9792 lm
Reported Efficacy (AC)	137 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	80
Reported R9	9
Reported IES Rf	83
Reported IES Rg	98
Reported IES Rcs,h1	-12
Reported Default Light Output	9792 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	72 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	72
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2022-08-26	Listed	5.1	Standard
------------	--------	-----	----------