

DESCRIPTION

Outlasting and outperforming 400W metal halide fixtures, this 200W LED area light is ideal for a variety of outdoor applications.

FEATURES

- Type III light distribution projects light outwards with a lateral width of 40 degrees
- Slipfitter adjusts up to 180° (90° left and 90° right)
- 0-10V dimming

LISTINGS

- IP65
- UL Listed for wet locations

PERFORMANCE

- CRI: >80
- CCT: 2200K
- Rated lifetime L70: 50,000 hours
- Surge Protection: 5kV
- Philips Lumileds LEDs
- Light Distribution: Type III
- BUG: B4-U0-G3

THERMAL

- -40°F to 113°F (-40°C to 45°C) operating temperature

ELECTRICAL

- THD: <20%
- Power Factor: >0.9
- Input Voltage: 120-277V
- Dimmable power supply (0-10V)

INSTALLATION

- Designed for mounting with the included slipfitter mount; see installation instructions for more information.

CONSTRUCTION

- Low profile die-cast aluminum housing
- Durable dark bronze powder coat finish

WARRANTY

- 5 year prorated warranty; see pltsolutions.com for warranty details

project name	type
catalog number	
comments	voltage
approved by	date



APPLICATIONS

- Parking Lots
- Automotive Dealerships
- Roadways
- Campuses
- Area Security Lighting
- Airports

PERFORMANCE SUMMARY

Item #	Watts	Lumens	LPW	CCT	CRI	Dimming	Voltage	Replaces	Light Distribution
PLTS-12312	200	20,000	100	2200K	>80+	0-10V	120-277V	MH400	Type III

DIMENSIONS



DIMENSIONS

Length: 19.65"

Length w/ Slipfitter: 26.46"

Height: 3.82"

Width: 13.11"

Weight: 13.67 lbs

Slipfitter Height: 6.89"

Slipfitter Width: 4.88"