

DESCRIPTION

Featuring a low-profile design, this 150W round LED high bay is a cost-effective solid state solution for high bay applications, providing a one-for-one replacement of 400 Watt metal halide fixtures.

FEATURES

- Up to 145 LPW ultra-high efficiency delivers superior performance over older HID high bays
- 0-10V dimming
- 6' power cord standard for more installation flexibility

LISTINGS

- UL Listed for wet locations
- IP65 Rated
- DesignLights Consortium® 5.1 Premium - meets the requirements for the highest DLC qualification for efficacy and lumen maintenance - PLTSN122412

PERFORMANCE

- CRI: >80
- Rated lifetime L70: ≥100,000 hours
- Philips Lumileds LEDs

THERMAL

- -40°F to 122°F (-40°C to 50°C) operating temperature

ELECTRICAL

- THD: ≥0.9
- Power Factor: ≤20%
- Input Voltage: 277-480V
- Surge Protection: 6kV
- Dimmable power supply (0-10V)

INSTALLATION

- Suspended mounting with included 10mm ring or surface mounting with u-bracket (sold separately); see installation instructions for more information
- S/MH(C0/C180): 1.30
- S/MH(C90/C270): 1.30

CONSTRUCTION

- Slim, lightweight die-cast aluminum construction (5.29 lbs) allows for quick and easy installation

project name	type
catalog number	
comments	voltage
approved by	date



WARRANTY

- 5 year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Warehouses
- Manufacturing Plants
- Distribution Centers
- Grocery Stores
- Gymnasiums
- Indoor Recreational Facilities
- Cold Storage
- Big Box Retail
- Service Repair Centers

PERFORMANCE SUMMARY

Item #	Model	Watts	Lumens	LPW	CCT	CRI	Dimming	Voltage	Replaces	DLC #	DLC Rating
PLT-11909	UFO	150	21,700	145	5000K	>80	0-10V	277-480V	MH400	PLTSN122412	5.1 Premium

MOUNTING ACCESSORIES

SKU	Description
PLTS-12377	Adjustable U-Bracket - White

DIMENSIONS



DIMENSIONS

Height (with ring mount): 6.2"

Diameter: 11.8"

Weight: 5.29 lbs

Ring Mount Thread Size: 10MM

PHOTOMETRICS

