2" MINIFIT MODULE













FEATURES


- Small 2" light aperture
- Compact form factor allows for shallow plenum installation
- Brushed metal and matte white trim finishes
- Up to 780 lumens delivered
- 2700K / 3000K / 4000K / 5000K CCT, 90 CRI
- 120V line voltage dimmable down to 10%
- Ambient temperature rating: -4°F / -20°C to 104°F / 40°C
- Damp location rated standard, wet location rated with glass trims

RetailOffice

- IC Rated and Title 24 compliant
- Rated L70 lifetime of 50,000 hours
- ETL listed
- Energy Star® listed
- 5 year warranty







BENEFITS



EXTENSIVE TRIM SELECTION

The 2" MINIFIT modules have a variety of field interchangeable trim options to compliment many different applications. Choose between deep or flat trim, white or brushed metal finishes, and open or glass enclosed lenses. The MINIFIT 2" module adds a fresh, clean, simple look to any lighting project.

QUICK AND EASY INSTALLATION

Installing the 2" MINIFIT modules is very simple. Connect the power to the driver box. Then attach the fixture with the quick connect cord and fasten it to the ceiling securely with the spring action clips.



ORDERING

Module						Trims		
Series	Size	CRI	ССТ	Beam Angle	Dimming	Trim	Style	Finish
MM Mini Module	2 2" 780lm	₹90 CRI90	☐ 27 2700K	Flood 38°	DIM120 120V - Line voltage dimming	MM2T MM2 Trim	RFT/OP Round Flat - Open	☐ WH White
			□ 30 3000K				RFT/GL Round Flat - Glass Cover	BM* Brushed Metal
			☐ 40 4000K				RDT/OP Round Deep - Open	
			□ 50 5000K				RDT/PN Round Deep - Pinhole	
							RDT/WW Round Deep - Wall Wash	

- Brushed Metal finish is only available for Round Flat trims.
- ** A complete fixture consists of two items, one module and one trim, ordered seperately.

ACCESSORY ORDERING INFORMATION							
Product	Model	Picture	Description				
98589	MM2NCPLATE		MINIFIT 2" Module New Construction Plate for Stud / Joist mounting				
35095	MM2CON6		MINIFIT 2" Module 6 foot extension cable				
35096	MM2CON20		MINIFIT 2" Module 20 foot extension cable				

