# **DesignLights Consortium**





Classification	Standard
Primary Use	Direct Linear Ambient Luminaires
Reported Input Wattage	25 W
Reported Light Output	3250 lm
Reported CCT	3500 K
Reported CRI (Ra)	83
Product ID	S-GCPXSM
DLC Family Code	<u>DDDLTU</u>
Listing Status	Listed
Date Qualified	2023-01-06

# PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting		
Technical Requirements Version	5.1		
Product ID	S-GCPXSM		
Manufacturer	Precision Lighting & Transformer, Inc		
Brand	PLT		
Model Number	PLTM92A142		
Parent	Yes		
Classification	Standard		
DLC Family Code	DDDLTU		
Length	2.0 ft		
Input Power Type	AC		

# PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires	
General Application	Linear Ambient	
Primary Use Designation	Direct Linear Ambient Luminaires	

### **PRODUCT CAPABILITIES VIEW DETAILS**

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	3250 lm
Reported Light Output	3230 1111
Reported Efficacy (AC)	130 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	83
Reported R9	10
Reported IES Rf	84
Reported IES Rg	94
Reported IES Rcs,h1	-12
Reported Minimum Light Output	2100 lm
Reported Maximum Light Output	3250 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	3250 lm

### REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	25 W
Reported Total Harmonic Distortion	3.1 %
Reported Power Factor	0.998
Reported Minimum Input Wattage	15 W
Reported Maximum Input Wattage	25
Reported Default Input Wattage	25

Voltage Range 120-277 V	voltage Range	120 211 V
-------------------------	---------------	-----------

#### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Tested Light Output	3204 lm
Tested Efficacy (AC)	128.31 lm/W
Tested CCT	3355 K
Tested CRI (Ra)	83
Tested R9	10
Tested IES Rf	84
Tested IES Rg	94
Tested IES Rcs,h1	-12 %
Tested Duv	0.00157

### **TESTED ELECTRICAL PERFORMANCE VIEW DETAILS**

Tested Voltage	120
Tested Input Wattage	25 W
Tested Total Harmonic Distortion	6.2 %
Tested Power Factor	0.942

#### **VERSION HISTORY VIEW DETAILS**

2023-01-06	Listed	5.1	Standard
------------	--------	-----	----------