# **DesignLights Consortium**





| Classification         | Standard                         |
|------------------------|----------------------------------|
| Primary Use            | Direct Linear Ambient Luminaires |
| Reported Input Wattage | 90 W                             |
| Reported Light Output  | 11700 lm                         |
| Reported CCT           | 3500 K                           |
| Reported CRI (Ra)      | 83                               |
| Product ID             | S-UYGBNI                         |
| DLC Family Code        | QQQVXT                           |
| Listing Status         | Listed                           |
| Date Qualified         | 2022-12-21                       |

### PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List         | Solid State Lighting                  |  |
|--------------------------------|---------------------------------------|--|
| Technical Requirements Version | 5.1                                   |  |
| Product ID                     | S-UYGBNI                              |  |
| Manufacturer                   | Precision Lighting & Transformer, Inc |  |
| Brand                          | PLT                                   |  |
| Model Number                   | PLTM989142                            |  |
| Parent                         | Yes                                   |  |
| Classification                 | Standard                              |  |
| DLC Family Code                | QQQVXT                                |  |
| Length                         | 8.0 ft                                |  |
| Input Power Type               | AC                                    |  |

# PRODUCT CATEGORIZATION VIEW DETAILS

| Category                | Indoor Luminaires                |  |
|-------------------------|----------------------------------|--|
| General Application     | Linear Ambient                   |  |
| Primary Use Designation | Direct Linear Ambient Luminaires |  |

#### **PRODUCT CAPABILITIES VIEW DETAILS**

| Integral Controls                      | No                                 |
|--|------------------------------------|
| Dimming Capability and Range           | Continuous Dimming to 10% or below |
| Integral Control Capability            | No Control Capability              |
| Sensor Type                            | No Sensor                          |
| SSL V5 Wired Communication Protocol    | 0-10V Analog                       |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol               |
| Field Adjustable Light Output          | No                                 |
| White-Tunable                          | Yes                                |
| Warm-Dimming                           | No                                 |
| Field Adjustable Light Distribution    | No                                 |

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output         | 11700 lm |
|-------------------------------|----------|
| Reported Efficacy (AC)        | 130 lm/W |
| Reported CCT                  | 3500 K   |
| Reported CRI (Ra)             | 83       |
| Reported R9                   | 7        |
| Reported IES Rf               | 83       |
| Reported IES Rg               | 98       |
| Reported IES Rcs,h1           | -12      |
| Reported Minimum Light Output | 11700 lm |
| Reported Maximum Light Output | 11700 lm |
| Reported Minimum CCT          | 3500 K   |
| Reported Maximum CCT          | 5000 K   |
| Reported Default Light Output | 11700 lm |

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage             | 90 W      |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 4.7 %     |
| Reported Power Factor              | 0.996     |
| Reported Maximum Input Wattage     | 90        |
| Reported Default Input Wattage     | 90        |
| Voltage Range                      | 120-277 V |

#### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

| Tested Light Output  | 11453 lm    |
|----------------------|-------------|
| Tested Efficacy (AC) | 127.42 lm/W |
| Tested CCT           | 3426 K      |
| Tested CRI (Ra)      | 82          |
| Tested R9            | 7           |
| Tested IES Rf        | 83          |
| Tested IES Rg        | 98          |
| Tested IES Rcs,h1    | -12 %       |
| Tested Duv           | -0.00086    |

#### **TESTED ELECTRICAL PERFORMANCE VIEW DETAILS**

| Tested Voltage                   | 120    |
|----------------------------------|--------|
| Tested Input Wattage             | 89.9 W |
| Tested Total Harmonic Distortion | 5 %    |
| Tested Power Factor              | 0.968  |

#### **VERSION HISTORY VIEW DETAILS**

| 2022-12-21 | Listed | 5.1 | Standard |
|------------|--------|-----|----------|
|------------|--------|-----|----------|