

L25-DC-CEC

25 Watt UL Listed LED Emergency Driver



Specifiers reference:

Project: _____

Type: _____

Model #: _____

Comments: _____

Product Summary

- Approvals** UL Listed to UL924
- Input** (Universal) 115 - 277Vac, 50/60 Hz
- Input current** 70 mA (max.)
- Input power** 5 Watts (max.)
- Output voltage** 15-55 Vdc - Class 2 Compliant
- Output power** 25W Constant Power
- Operating time** 90 minutes
- Battery** Lithium
- Test Switch** Quick Connect IP65 rated illuminated test switch
- Weight** 3.4 lbs.
- Case** Galvanized steel
- Dimensions** 13.3" L x 2.44" W x 1.49" H
- Operating Temperature** 32° to 131° F (0° to 55° C)
- Remote Mounting Distance** 18 feet
- Recharge time** 24 Hrs
- Warranty** 5 years full

Description

The Assurance Emergency Lighting L25-DC-CEC LED emergency drivers are used with LED luminaires and Class 2 LED drivers to convert lighting fixtures for emergency lighting applications.

Specifications

Emergency lighting shall be provided by using a standard LED fixture, separate LED Class 2 driver and a constant power L25-DC-CEC 25W emergency LED Driver. The LED emergency driver shall be UL Listed for field or factory installations. It allows the LED luminaire to be used for both normal and emergency operation. The luminaire can be used for switched or unswitched applications. The L20-DC-CEC emergency driver contains battery, charger and DC converter in a metal can. The L25-DC-CEC emergency driver shall provide a constant 25 watts to the LED load for a minimum of 90 minutes. A quick connect IP65 rated test switch shall be included. The L25-DC-CEC shall have 5 watts of input power (max). The L25-DC-CEC meets or exceeds all National Electrical Code and Life Safety Code Emergency Lighting requirements and is rated for damp locations. The L25-DC-CEC LED emergency drivers are warranted for a full 5 years from date of purchase. The L25-DC-CEC meets Title 20 CEC requirements.



Note: Output current of AC driver must not exceed 5.0A

Mounting Configuration



L25-DC-CEC: Dual flex conduit on each end, with test switch and plate

All Specifications subject to change without prior notification.