

**DESCRIPTION**

Featuring selectable wattage and color temperatures that allow you to adjust the light output as needed, these LED mini wall packs are an efficient choice for improving security lighting in outdoor areas.

**FEATURES**

- Delivers up to 135 LPW depending on the wattage selected
- Replaces 50-70W metal halide fixtures
- Integrated photocell for dusk till dawn operation
- Wattage and color temperature are adjusted via dip switch inside of fixture; see installation instructions for more information.

**LISTINGS**

- IP65 Rated
- UL Listed for wet locations
- BUG: B1-U3-G2
- DesignLights Consortium® 5.1 Premium - meets the requirements for the highest DLC qualification for efficacy and lumen maintenance; DLC PN - PLTSN311311W

**PERFORMANCE**

- CRI: 80+
- CCT: 3000K to 5000K
- LED L70 Lifetime: 100,000 Hours
- Philips Lumileds SMD LEDs

**ELECTRICAL**

- THD: ≤ 20%
- Power Factor: ≥ 0.9
- Input Voltage: 120-277V

**THERMAL**

- -40°F to 113°F (-40°C to 45°C) operating temperature

**CONSTRUCTION**

- Die-cast aluminum housing with white finish
- Polycarbonate lens

**WARRANTY**

- 5 year limited warranty; see [pltsolutions.com](http://pltsolutions.com) for warranty details

project name	type
catalog number	
comments	voltage
approved by	date



**APPLICATIONS**

- Security Lighting
- Pedestrian Lighting
- Parking Areas

# PERFORMANCE SUMMARY

Item #	Watts*	Lumens*	LPW	CRI	CCT*	Lens	Voltage	Replaces	DLC Level	DLC #
PLTS-11948	8/10/15	1077/1342/2033	134/134/135	80+	3000K/4000K/5000K	Polycarbonate	120-277V	MH50-70	5.1 Premium	PLTSN311311W

\*See Selectable Table for full breakdown

## SELECTABLE TABLE

Wattage	CCT	Lumens	Efficacy
8	3000K	1008	126
	4000K	1077	134
	5000K	1048	131
10	3000K	1274	127
	4000K	1342	134
	5000K	1325	132
15	3000K	1901	126
	4000K	2033	135
	5000K	1978	131

## DIMENSIONS



### **DIMENSIONS**

Length: 5.8"

Height: 8.6"

Width: 3.09"

Weight: 1.3 lbs.