

145 West Commercial Ave. Moonachie, NJ 07074 T: 800.528.5555

F: 800.441.7708 www.bulbrite.com



4.5W LED T6 3000K FILAMENT E12 CLEAR FULLY COMPATIBLE DIMMING

Item #776791

Ordering Code LED4T6/30K/FIL/3

UPC 739698901572

- Full glass enclosure to provide the proper shape and size of the incandescent counterpart.
- Utilizes LED filaments to provide a decorative look and feel.
- Commonly used in pendants, chandeliers, and sconces.
- Fully compatible with all dimmer types.
- Also available with amber finish.









TECHNICAL SPECIFICATIONS

Item # 776791	Watts 4.5	Bulb Type T6	Base E12	Volts 120	Finish/Description Clear	Beam Angle (°) 320	Color Temperature (CCT) 3000K
Color Soft White Light	CRI 90	Lumens 450	CBCP N/A	Average Hours 15000	M.O.L. (inches) 3.34	M.O.D. (inches) 0.78	Incandescent Equivalent 40
Energy Star N	DLC N	Title 24 Compliant	: Safety Rated UL	Safety Rating Typ	eEnclosed Rated Y	Dimmable Y	Warranty 5

Order Multiple

5

APPLICATION SUGGESTIONS









Sign / Display



Dimmer Compatibility Guide

Product Family Name:

Ordering Code: Item Number: Ordering Code: 776780 LED4T6/27K/FIL/3 776791 LED4T6/27K/FIL/3

Lamps per Dimmer

					Recommended	Maximum	
	Manufacturer	Product	Model Number	Overall Rating	Minimum	Tested*	Notes
		IllumaTech	IPI06	Best	1	6	Dims down to 1%
	Leviton	SureSlide	6633-P	Good	1	6	Dead travel Med to LE with 1
		Vizia	VPI06-1LZ	Good	1	6	Flickering at LE with 2
		Toggler	TG-600	Best	1	6	Dims down to 1%
Incandescent/Halogen (Triac/Phase		Lumea	LGCL-600	Best	1	6	Dims down to 1%
Cut/Leading Edge Dimmers)	Lutron	Diva	DV-600	Best	1	6	Dims down to 1%
		Skylark	S-600	Best	1	6	Dims down to 1%
		Maestro	MAW-600	Not compatible	1	6	
		Titan	CD703-PW	Bad	4	6	Not works with full range dimming with 1-3
	Legrand	Harmony	D703-PTC	Bad	4	6	Not works with full range dimming with 1-3
		Harmony	H703-PTC	Bad	4	6	Not works with full range dimming with 1-3
		I	I a.a				I-1 1
		IllumaTech	IPL06	Best	1	6	Dims down to 1%
	Leviton	Sureslide	6674	Best	1	6	Dims down to 1%
		Decora	6672	Best	1	6	Dims down to 1%
		Decora Slide	DSL06-1LZ	Best	1	6	Dims down to 1%
		Skylark	CTCL-153	Best	1	6	Dims down to 1%
071 /1 70		Diva	DVCL-153PL	Best	1	6	Dims down to 1%
CFL/LED	Lutron	Maestro	MACL-153MLH	Best	1	6	Dims down to 1%
		Skylark	SCL-153P	Best	1	6	Dims down to 1%
		Toggler	TGCL-153PH	Best	1	6	Dims down to 1%
		Radio RA	RA2RR-6CL-PD	Best	1	6	Dims down to 1%
		Harmony	DCL453-PTC	Best	1	6	Dims down to 1%
	Legrand	Radiant	RHCL453PW	Best	1	6	Dims down to 1%
		Adorne Paddle	ADPD453LM2	Best	1	6	Dims down to 1%
							_
		Vizia	VPE04	Best	1	6	Dims down to 1%
	Leviton	IllumaTech	IPE04	Good	1	6	Reverse dimming from HE to Med
		Decora	6615-P	Bad	1	6	Reverse dimming from HE to Med. Dims down to 35%
		Skylark Countour	CTELV-303P	Best	1	6	Dims down to1%
Electronic Low Voltage		Diva	DVELV-300P	Best	1	6	Dims down to1%
	Lutron	Maestro	MAELV-600	Best	1	6	Dims down to1%
		Skylark	SELVB-300P	Best	1	6	Dims down to1%
		VIERTI	VTEL-600M-W	Best	1	6	Dims down to1%
	Legrand	Scene Director	SCELV	Bad	1	6	Flickering at HE with 1-6.dims down to 3%
	Leviton	Vizia	VPM-06	Good	1	6	Flickering at HE with 1-6
	2011011	Decora	6613-P	Best	1	6	Dims down to 1%
Magentic Low Voltage	Lutron	Maestro	MALV-600	Not compatible	1	6	
		Harmony	DLV703-PW	Good	2	6	Dims down to 1%
	Legrand	Titan	CDLV703-PW	Good	2	6	Dims down to 1%
Smart Dimmer	Leviton	Decora Digital (Bluetooth)	DDMX1-BLZ	Best	1	6	Dims down to 1%
	Leviton	Decora Smart Z-Wave Technology	DZ6HD	Best	1	6	Dims down to1%
	Leviton	Decora Smart WiFi Technology	DW1KD	Best			Dims down to1%
	Lutron	Caseta Wireless smart dimmer Wi-Fi	PD-10NXD	Best	1	6	Dims down to1%
	Lutron	Caseta Wireless smart dimmer Wi-Fi	PD-6WCL	Best	1	6	Dims down to1%
	GE	Z WAVE	ZW3005	Good	1	6	Minor flickering at LE with 1-6
Universal		Adorne SofTap	ADTP703TU	Good	3	6	Dims down to 16%
		Miro Decorator	DRD4-W	Not compatible	1	6	It doesn't turn off with 1-6
	Legrand	Harmony	H703PTUTC	Bad	3	6	Dims down to 25%
		Adorne Whisper	ADWR700MMTUW2	Best	1	6	Dims down to 1%
		Adorne Touch	ADTH700MMTUM2	Best	1	6	Dims down to 1%
	Cooper	Decorator	DAL06P-C2-K-L	Good	2	6	Dims down to 1%
	Соорег	Skye	SAL06P-W-K-L	Good	2	6	Dims down to 1%

*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.
†May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating				
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.			
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.			
	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light lev These periods of dead travel are minor and most of the time not visible. Minor audible noise.			
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output.			
High End (H.E.) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.			
Low End (L.E.) Dead Travel	Determines now much, if any, usad traver exists at the top and bottom of the diffinite shall be moved without anecting the light level.			

Contact Information:
Bulbrite industries inc.
145 West Commercial Avenue
Moonachie, New Jersey 07074
PHONE: 1-800-528-5555
FAX: 1-800-441-7708
Email: ProductSupport@bulbrite.com
©2017 Bulbrite industries inc.
All Rights Reserved.