

In-Wall Timer - Ascend® Standard 7-Day Programmable Timer, 120 VAC, 15A, White

Item ST700W



COL COLUS

PRODUCT DESCRIPTION

The Ascend Standard In-Wall Timer is a 7-Day Programmable Timer featuring a sleek, modern design. The timer can be configured in minutes using a large backlit LCD display and includes pre-programmed templates for easy use. The Ascend Standard features Astronomic dusk-to-dawn settings and automatic Daylight Saving Time adjustments. Neutral required. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- Quick, intuitive installation
- ► Single-pole or 3-way switches
- Sleek, Modern Design
- ► 7-Day Timer with Automatic Daylight Saving and Astronomic ON/OFF at Dusk or Dawn
- Intuitive Setup
- ► Three pre-programmed schedule templates for convenience
- ► Fully customized scheduling for flexibility
- Program up to 42 unique events
- ► Large, easy-to-read backlit LCD screen
- > Non-replaceable battery backup keeps time and date information in the event of a power loss

APPLICATIONS

- Indoor Lighting Control
- Air Movement & Ventilation
- Outdoor Lighting Control

TECHNICAL DATA

General	
Model Number	ST700W
Description	Ascend® Standard 7-Day Programmable Timer, 120 VAC, 15A, White
UPC Code	078275149083
Brand	Intermatic
Country of Origin (Intermatic)	THAILAND
Warranty Period	3-Year limited
Control Specifications	
Minimum 0N/0FF Times	1 min
Maximum ON/OFF Operations	42
Operation Mode	24 hour; 7 day
Operation Features	Astronomic; Daylight Saving Time
Mechanism Type	Digital/Electrical
Backup Type	Battery
Battery Type	CR2032
Battery Service Type	Non-replaceable
Application Compatibilities	CFL; Fluorescent; Incandescent; LED

Mechanical Specifications

Wall Plate Configurations

Single-Gang



Dimensions	
Product Dimensions (H x W x D) in	2 3/4 x 1 3/4 x 1 1/3 in
Material Specifications	
Color	White
Load Ratings	
General Purpose	15 A
Electronic Ballast LED	5 A, 600 W
Motor Load Ratings Ranges	1 HP, 120 VAC, 50/60 Hz
Tungsten Load Ratings	8 A
Inductive Load Ratings Ranges	15 A, 120 VAC, 50/60 Hz
Incandescent Load Ratings (Multi-Gang)	8 A, 120 VAC, 50 Hz; 8 A, 60 Hz
Incandescent Multi Gang Load Ratings Ranges	8 A, 120 VAC, 50/60 Hz
Electrical Specifications	
Input Voltage Range(s)	120 VAC, 50/60 Hz
Wiring Configurations	3-Way; Single
Neutral Connection Required	Yes
Environmental Specifications	
Temperature (operation)	-4 - 122 °F / -20 - 50 °C
Packaging	
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.5 in
Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	Title 20
California Proposition 65	DEHP