

LED PAR LAMPS

277V PAR30LN & PAR38 SERIES



13W PAR30 Long Neck



17W PAR38

PRODUCT DESCRIPTION:

Engineered to operate strictly on 277-volt electrical systems, PAR38 and long-neck PAR30 lamps are an energy-efficient replacement for conventional halogen bulbs in retail, hospitality and architectural applications where converting voltage would be costly or labor intensive.

Suitable for spot or general lighting, the lamps feature instant-on technology and deliver a high-quality light with excellent color rendering for applications such as shops, lobby and reception areas, corridors, stairways and washrooms.

FEATURES:

• 277V

c **FLI**°us

FC

RoHS

- 40° beam angle
- 25,000 Hour life at L70 standards
- CRI: >80
- High output chip-on-board LED
- Non-dimmable
- Operating temperature range: 4° to 104° F
- Not for use in enclosed luminaires
- Five year warranty

MODEL SELECTION (Full list of order codes on pg. 2)	Typical order example: 13P30LNLED230FL					
	LED	2		FL		
FAMILY DIMMABILITY		VOLTAGE	COLOR TEMPERATURE (CCT)	BEAM ANGLE		
13P30LN= 13 watts, PAR30 Long neck 17P38= 17 watts, PAR38	LED= Non-Dimmable	2= 277V	30= 3000K 40= 4000K	FL= Flood 40°		



LED PAR LAMP277V PAR30LN & PAR38 Series

Page: 2 of 2

SPECIFICATIONS:		13P30LNLED230FL	13P30LNLED240FL	17P38LED230FL	17P38LED240FL		
ITEM	SPECIFICATION	DET	AILS	DETAILS			
GENERAL PERFORMANCE	Color Temperature	3000K	4000K	3000K	4000K		
	Lumens Delivered (lm)	1,000	1,200	1,700	1,800		
	Efficacy (lm/w)	77	92	100	106		
	Equivalency	90W	90W	120W	120W		
	Lumen Maintenance (L70)	25,000 Hours					
ELECTRICAL	Power Factor	≥.90					
	Input Voltage	277V					
PHYSICAL	Operating Temperature	-4° F to 104° F					
APPLICATION	Environment	Dry, Damp					
	Warranty	5 Year					

ORDERING:

ORDER CODE	MODEL	WATTAGE	INCANDESCENT EQUIVALENCY	CRI	OUTPUT (LUMENS)	CBCP (cd)	DIMENSIONS L" X W"	сст	BEAM ANGLE
PAR30 LONG NECK									
74686	13P30LNLED230FL	13W	90W	82	1,000	1700	4.53" x 3.75"	3000K	40°
74645	13P30LNLED240FL	13W	90W	82	1,200	2100	4.53" x 3.75"	4000K	40°
PAR38									
74687	17P38LED230FL	17W	120W	82	1,700	1900	5.10" x 4.75"	3000K	40°
74692	17P38LED240FL	17W	120W	82	1,800	2300	5.10" x 4.75"	4000K	40°

Please contact your MaxLite representative to order products that don't have order codes listed here. Lighting layouts and spacing criteria available upon request