

DesignLights Consortium



Classification	Standard
Primary Use	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	35 W
Reported Light Output	3850 lm
Reported CCT	3500 K
Reported CRI (Ra)	83
Product ID	S-86RV3K
DLC Family Code	EEEHDM
Listing Status	Listed
Date Qualified	2023-03-24

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-86RV3K
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PRECISION LIGHTING & TRANSFORMER INC
Model Number	PLTRD1111
Parent	Yes
Classification	Standard
DLC Family Code	EEEHDM
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer
Primary Use Designation	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming above 10%
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	3850 lm
Reported Efficacy (AC)	110 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	83
Reported R9	7
Reported IES Rf	84
Reported IES Rg	94
Reported IES Rcs,h1	-12
Reported Minimum Light Output	2750 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	3850 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	35 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	25 W
Reported Maximum Input Wattage	35
Reported Default Input Wattage	35 W

Voltage Range	110-347 V
---------------	-----------

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	3747 lm
Tested Efficacy (AC)	110.86 lm/W
Tested CCT	3400 K
Tested CRI (Ra)	83
Tested R9	7
Tested IES Rf	84
Tested IES Rg	94
Tested IES Rcs,h1	-12 %
Tested Duv	-0.0002

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	33.8 W
Tested Total Harmonic Distortion	16.6 %
Tested Power Factor	0.884

VERSION HISTORY VIEW DETAILS

2023-03-24	Listed	5.1	Standard
------------	--------	-----	----------