

DesignLights Consortium



Classification	Standard
Primary Use	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	35 W
Reported Light Output	3850 lm
Reported CCT	3500 K
Reported CRI (Ra)	80
Product ID	PLTLJDCSK8QW
DLC Family Code	LLLBYR
Listing Status	Listed
Date Qualified	2021-08-04

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PLTLJDCSK8QW
Manufacturer	Halco Lighting Technologies
Brand	ProLED
Model Number	BPL-22-WS-CS-U
Parent	Yes
Classification	Standard
DLC Family Code	LLLBYR
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer
Primary Use Designation	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	3850 lm
Reported Efficacy (AC)	110 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	80
Reported R9	7
Reported IES Rf	84
Reported IES Rg	98
Reported IES Rcs,h1	-12
Reported Minimum Light Output	2200 lm
Reported Maximum Light Output	3850 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	3850 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	35 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	20 W
Reported Maximum Input Wattage	35
Reported Default Input Wattage	35 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	4166.43 lm
Tested Efficacy (AC)	123.78 lm/W
Tested CCT	3402 K

Tested CRI (Ra)	83
Tested R9	7
Tested IES Rf	84
Tested IES Rg	98
Tested IES Rcs,h1	-12 %
Tested Duv	0.0005

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	33.66 W
Tested Total Harmonic Distortion	7.86 %
Tested Power Factor	0.9113

VERSION HISTORY VIEW DETAILS

2021-08-05	Listed	5.1	Standard
2021-08-04	Listed	5.1	Standard