2.94 in (75 mm)



Shown actual size: Diva preset dimmer and 1-gang Claro wallplate in White (WH).

Product family features

- · Large paddle switch with a captive linear slide dimmer for a standard Designer wallplate opening
- Preset dimmer
- LED+, reverse-phase, and 0-10V models available
- · Coordinating Claro, Satin Colors, and Stainless Steel wallplates only available separately
- All models must be derated unless otherwise noted. Visit **lutron.com/multigang** for more information.

Control types

1 3-way or 4-way (2 or more locations)

Direct load type compatibility

Dimmable LED/CFL lighting (screw-base)

Incandescent/halogen lighting

Magnetic low-voltage lighting

Electronic low-voltage lighting

LED lighting

Switched lighting/fan/motor

Ceiling fans

Load type requiring load interface

Neon/cold cathode lighting

Lighting load interfaces may be required for some additional load type, voltage, and capacity combinations. For additional information see "Lighting Load Interfaces."

Available finishes

Use **BOLD** color code in model number (Example: DV-600P-BR) Gloss





Stainless Steel metal wallplate only available separately and includes black plastic trim/adapter, visible from side. Match with separate Black (BL) or Midnight (MN) controls.



Mechanical switches



- Paddle turns on/off
- Use with any 15 A load
- General purpose switching of all light sources and motor loads
- Available with locator light

▲ General purpose switches

Mechanical switches

Single-pole	CA-1PS- XX 1
120/277V 15A	SC-1PS- <u>XX</u> 2
3-way	CA-3PS- XX 1
120/277V 15A	SC-3PS- <u>XX</u> ²
4-way	CA-4PS- XX 1
120/277V 15A	SC-4PS- <u>XX</u> 2

Mechanical switches with locator light

Single-pole	CA-1PSNL-XX3
120V 15A	SC-1PSNL-XX4
3-way	CA-3PSNL-XX3
120V 15A	SC-3PSNL-XX4
4-way	CA-4PSNL-XX3
120V 15A	SC-4PSNL-XX4

No derating required if ganged.

XX1: Gloss color codes

XX²: Satin color codes

XX³: Available in Gloss White (WH), Ivory (IV), Almond (AL), and Light Almond (LA)

XX⁴: Available in Satin Colors Snow (SW), Biscuit (BI), Eggshell (ES), Goldstone (GS), Limestone (LS), and Sea Glass (SG)

Wallplates not included. Order separately.

Fan controls



- · Paddle turns fan on/off
- · Slide up to increase speed, down to decrease speed
- 3 quiet fan speeds for increased comfort
- · For use with only one ceiling paddle fan
- Designed to prevent motor hum

Fan controls

Fan controls—quiet 3-speed

DVFSQ-F-XX1 3-way/single-pole 120V 1.5A DVSCFSQ-F-XX2 3-way/single-pole DVFSQ-F-HO-XX1 120V 2A

DVFSQ-F-HO model for use with Hunter Original Series fans.

Does not include built-in locator light. No derating required if ganged.

Fan/light controls



Switch (paddle)

· Turns light on/off

Fan Control (slider)

- · Use slide to turn fan on/off and adjust fan speed
- 3 quiet fan speeds for increased comfort
- For use with only one ceiling paddle fan
- · Designed to prevent motor hum

★ Fan/light controls

Fan/light controls—quiet 3-speed

Single-pole DVFSQ-LF-XX1 DVSCFSQ-LF-XX² 120 V 1.5 A Fan, 120V 1A LED/CFL,

2A Incandescent/halogen

No derating required if ganged.

Does not include built-in locator light.

XX1: Gloss color codes XX²: Satin color codes

Wallplates not included. Order separately.