

DesignLights Consortium



Classification	Standard
Primary Use	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	45 W
Reported Light Output	5000 lm
Reported CCT	3500 K
Reported CRI (Ra)	83
Product ID	S-DNRTA8
DLC Family Code	QQQVYB
Listing Status	Listed
Date Qualified	2023-01-24

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-DNRTA8
Manufacturer	LEDVANCE, LLC (formerly OSRAM SYLVANIA, INC)
Brand	LEDVANCE
Model Number	PANELF3BS045UNVD8SC724GWHTAA
Parent	No
Classification	Standard
DLC Family Code	QQQVYB
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer
Primary Use Designation	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	5000 lm
Reported Efficacy (AC)	110 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	83
Reported R9	6
Reported IES Rf	85
Reported IES Rg	96
Reported IES Rcs,h1	-12
Reported Minimum Light Output	3300 lm
Reported Maximum Light Output	5000 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	5000 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	45 W
Reported Total Harmonic Distortion	0.2 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	30 W
Reported Maximum Input Wattage	45
Reported Default Input Wattage	45 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2023-01-24	Listed	5.1	Standard
------------	--------	-----	----------