



Replace existing fluorescent vapor tight fixtures with these LED ready vapor tight fixtures and customize the light output with 4 ft. LED T8 tubes of your choice.

DESCRIPTION

- Cost-effective LED ready vapor tight
- Perfect for loading docks, stairwells, and utility lighting
- Utilizes 2 single-ended direct wire 4 ft. LED T8 tubes (sold separately), allowing for the light output and color temperature to be customized as needed

LISTINGS

- UL Listed for dry locations
- IP65

ELECTRICAL

- Input Voltage: 120-277V
- Pre-wired non-shunted sockets

INSTALLATION

- Designed for surface or suspended mounting with mounting brackets, V-hooks, anchor & screws, and strain relief included; see installation instructions for more information

CONSTRUCTION

- Polycarbonate housing with light gray finish and stainless steel latches
- PC lens

WARRANTY

- 3-year limited warranty; see pltsolutions.com for warranty details

project name	type
catalog number	
comments	voltage
approved by	date



APPLICATIONS

- Utility Lighting
- Stairwell Lighting
- Parking Garages
- Hallways

ELECTRICAL	Lamp Type (Not Included)	T8 Single-Ended Direct Wire LED Lamps
	Number of Lamps	2
	Input Voltage	120 – 277V
CONSTRUCTION	Housing	Polycarbonate
	Lens	PC
	Base Power Supply	Hard wired for Single-Ended Direct Wire T8 LED Lamps
	Finish	Light Gray
LISTINGS	Certifications	UL Listed; IP65
	Environment	UL Dry Location Rated

PERFORMANCE SUMMARY

Item #	Length	Width	Height	Voltage	Warranty	Compatible Lamps
PLT-90312	50.4"	7.4"	3.9"	120-277V	3 Years	Single-Ended Direct Wire T8 LED Lamps

DIMENSIONS



DIMENSIONS

Length: 50.4"

Height: 3.9"

Width: 7.4"