

Project Name:	Type:
Part Number:	Date:

# HIGH CRI A LAMP Family

## FEATURES

- Suitable to replace 40W, 60W, 75W, 100W incandescent
- High CRI and R values (R9 50, R13 95) deliver richer reds and natural skin tones
- Tight LED binning for consistent CCT across all lamps
- Comfortable diffused light
- Smooth dimming with most forward and reverse phase dimmers\*
- Available in 2700K, 3000K, 3500K, 4000K and 5000K color temperatures
- Suitable for use in totally enclosed fixtures and damp locations\*\*
- Fixture operating temperature: -4°F to 95°F (-20°C to 35°C)
- Lamp ambient temperature: -4°F to 113°F (-20°C to 45°C)
- Rated Lifetime (L70): 25,000hrs
- 5 year limited warranty for 60W 277V equivalents
- 3 year limited warranty for the other equivalents \*\*\*



012823



## SPECIFICATIONS

Product	Model	Equiv.	Wattage (W)	CCT	Lumens	Efficacy (LPW)	Input Voltage	Beam Angle	CRI	Dim.*	Power Factor	Base	Fixture Rating	ES / JA8 / T20
36552	6A19DIM/927	40W	6	2700K	480	90	120V	230°	92	Yes	0.7	E26	Enclosed	√ / N.A. / √
36553	6A19DIM/930	40W	6	3000K	480	90	120V	230°	92	Yes	0.7	E26	Enclosed	√ / N.A. / √
36554	9A19DIM/927/R	60W	9	2700K	800	89	120V	230°	92	Yes	0.7	E26	Enclosed	√ / N.A. / √
36555	9A19DIM/930/R	60W	9	3000K	820	91	120V	230°	92	Yes	0.7	E26	Enclosed	√ / N.A. / √
36560	9A19DIM/935/R	60W	9	3500K	840	93	120V	230°	92	Yes	0.7	E26	Enclosed	√ / N.A. / √
36556	9A19DIM/940/R	60W	9	4000K	860	96	120V	230°	92	Yes	0.7	E26	Enclosed	√ / N.A. / √
36557	9A19DIM/950/R	60W	9	5000K	860	96	120V	230°	92	Yes	0.7	E26	Enclosed	√ / N.A. / √
36675	9A19DIM/927/GU24/RC	60W	9	2700K	800	89	120V	230°	92	Yes	0.7	GU24	Enclosed	√ / N.A. / √
36676	9A19DIM/930/GU24/RC	60W	9	3000K	820	91	120V	230°	92	Yes	0.7	GU24	Enclosed	√ / N.A. / √
36677	9A19DIM/940/GU24/RC	60W	9	4000K	860	96	120V	230°	92	Yes	0.7	GU24	Enclosed	√ / N.A. / √
36678	9A19DIM/950/GU24/RC	60W	9	5000K	860	96	120V	230°	92	Yes	0.7	GU24	Enclosed	√ / N.A. / √
98562	9A19/927/277V	60W	9	2700K	800	89	120-277V	240°	92	No	0.9	E26	Enclosed	√ / N.A. / √
98563	9A19/930/277V	60W	9	3000K	820	91	120-277V	240°	92	No	0.9	E26	Enclosed	√ / N.A. / √
98564	9A19/940/277V	60W	9	4000K	860	96	120-277V	240°	92	No	0.9	E26	Enclosed	√ / N.A. / √
36679	11A19DIM/927/R	75W	11	2700K	1,100	100	120V	230°	92	Yes	0.7	E26	Enclosed	√ / N.A. / √
36680	11A19DIM/930/R	75W	11	3000K	1,150	105	120V	230°	92	Yes	0.7	E26	Enclosed	√ / N.A. / √
36681	11A19DIM/940/R	75W	11	4000K	1,200	109	120V	230°	92	Yes	0.7	E26	Enclosed	√ / N.A. / √
36682	11A19DIM/950/R	75W	11	5000K	1,200	109	120V	230°	92	Yes	0.7	E26	Enclosed	√ / N.A. / √
98147	15A21DIM/927/N	100W	15	2700K	1,600	107	120V	240°	92	Yes	0.9	E26	Enclosed	√ / √ / √
98148	15A21DIM/930/N	100W	15	3000K	1,650	110	120V	240°	92	Yes	0.9	E26	Enclosed	√ / √ / √
98149	15A21DIM/940/N	100W	15	4000K	1,700	113	120V	240°	92	Yes	0.9	E26	Enclosed	√ / √ / √

\* This lamp might not be compatible with all dimmers and low-voltage transformers. Please visit [www.greencreative.com](http://www.greencreative.com) for compatibility information.


\*\* All High CRI A lamps are not suitable for use in IC enclosed fixtures.

\*\*\* Please visit [www.greencreative.com](http://www.greencreative.com) for Limited Warranty terms.




# HIGH CRI A LAMP Family


## DIMENSIONS & WEIGHT




Model	Base	MOL	Dia.	Weight
6A19DIM/xxx	E26	4-5/16"	2-3/8"	0.067lb




Model	Base	MOL	Dia.	Weight
9A19DIM/xxx/R	E26	4-3/8"	2-3/8"	0.067lb
11A19DIM/XXX/R	E26	4-5/16"	2-3/8"	0.067lb



Model	Base	MOL	Dia.	Weight
9A19/xxx/277V	E26	4-1/2"	2-3/8"	0.12lb



Model	Base	MOL	Dia.	Weight
9A19DIM/xxx/GU24/RC	GU24	4-3/16"	2-3/8"	0.101lb



Model	Base	MOL	Dia.	Weight
15A21DIM/xxx/N	E26	5-7/16"	3"	0.23lb



# HIGH CRI A LAMP Family

## MINIMUM COMPARTMENT DIMENSIONS\*\*\*

Model	Diameter	Height
6A19DIM/xxx	5-1/8"	7-1/2"
9A19DIM/xxx/R		
11A19DIM/xxx/R		
9A19/xxx/277V		
9A19DIM/xxx/GU24/RC		
15A21DIM/xxx/N		

\*\*\*Installing lamp in a fixture that does not have the minimum compartment dimensions will void the warranty and could cause product failures.

Where xxx means 824-965 which indicates CRI and color temperature

## ORDERING INFORMATION

Model	Master Carton			Shipping Carton		
	Case Qty	Case Dimensions (L x W x H)	Case Weight	Case Qty	Case Dimensions (L x W x H)	Case Weight
6A19DIM/xxx	N.A.	N.A.	N.A.	72PCS	14-9/16" x 14-9/16" x 10-7/16"	9.81 lb
9A19DIM/xxx/R	N.A.	N.A.	N.A.	72PCS	14-9/16" x 14-9/16" x 10-7/16"	11.46 lb
9A19DIM/xxx/GU24/RC	N.A.	N.A.	N.A.	72PCS	15-3/8" x 15-1/8" x 10-1/4"	12.13 lb
9A19/xxx/277V	6PCS	7-13/16" x 5-1/8" x 5-1/16"	1.28 lb	24PCS	15-13/16" x 11" x 5-15/16"	5.95 lb
9A19DIM/xxx	6PCS	7-5/8" x 5-1/8" x 4-15/16"	1.1lb	24PCS	15-15/16" x 11" x 5-13/16"	5.29lb
11A19DIM/xxx	6PCS	7-5/8" x 5-1/8" x 4-15/16"	1.21lb	24PCS	15-15/16" x 11" x 5-13/16"	5.95lb
11A19DIM/xxx/R	N.A.	N.A.	N.A.	72PCS	14-9/16" x 14-9/16" x 10-5/8"	10.58 lb
15A21DIM/xxx/N	6PCS	9-3/4" x 6-9/16" x 6-1/4"	2.2 lb	24PCS	19-9/16" x 13-9/16" x 7-1/8"	9.92 lb

Where xxx means 824-965 which indicates CRI and color temperature

## CERTIFICATION INFORMATION

Product	Model	ES ID#
36554	9A19DIM/927/R	2384790
36555	9A19DIM/930/R	2384791
36560	9A19DIM/935/R	2384792
36556	9A19DIM/940/R	2384793
36557	9A19DIM/950/R	2384794
36675	9A19DIM/927/GU24/RC	2386727
36676	9A19DIM/930/GU24/RC	2386728
36677	9A19DIM/940/GU24/RC	2386729
36678	9A19DIM/950/GU24/RC	2386730
36679	11A19DIM/927/R	2386731
36680	11A19DIM/930/R	2386732
36681	11A19DIM/940/R	2386733
36682	11A19DIM/950/R	2386734

Note: All rights reserved. All sizes and specifications are subject to change at any time without notice.



# HIGH CRI A LAMP Family

## MODEL

Model: 6A19DIM/xxx  
 9A19DIM/xxx/R  
 9A19DIM/xxx/GU24/RC  
 11A19DIM/xxx/R  
 15A21DIM/xxx/N

Where xxx means 824-965 which indicates CRI and color temperature



## DIMMER COMPATIBILITY

Model: 6A19DIM/xxx

Brand	Series	Model	Load (W)	Dimming Range	Dimmability
Lutron	Maestro	MAELV-600	600	20-100%	Compatible
	Nova	NTELV-600	600	10-100%	Compatible
	Diva	DV-600P	600	10-100%	Compatible
	Toggler	TG-600P	600	10-100%	Compatible
	Caseta	PD-5NE	250	10-100%	Compatible*
	Skylark Contour	CTELV-303P	300	10-100%	Compatible
	Diva	DVELV-300P	300	10-100%	Compatible
	Skylark Contour	CTCL-153P	150	10-100%	Compatible
	Diva	DVCL-153P	150	10-100%	Compatible
	Maestro C•L	MACL-153M	150	10-100%	Compatible
Leviton	IllumaTech	IPE04-1LZ	300	-	Not Compatible
	Sureside Decora	6674	600	10-100%	Compatible
	Trimatron	6602	600	10-100%	Compatible
Cooper	Aspire	9536	1,000	-	Not Compatible

\*Minimum 2 lamps



# HIGH CRI A LAMP Family

## DIMMER COMPATIBILITY

Model: 9A19DIM/xxx/R

Brand	Series	Model	Load (W)	Dimming Range	Dimmability
Lutron	Maestro	MAELV-600	600	20-100%	Compatible
	Nova	NTELV-600	600	10-100%	Compatible
	Diva	DV-600P	600	10-100%	Compatible
	Toggler	TG-600P	600	10-100%	Compatible
	Caseta	PD-5NE	250	20-100%	Compatible*
	Skylark Contour	CTELV-303P	300	10-100%	Compatible
	Diva	DVELV-300P	300	10-100%	Compatible
	Skylark Contour	CTCL-153P	150	10-100%	Compatible
	Diva	DVCL-153P	150	10-100%	Compatible
	Maestro C•L	MACL-153M	150	10-100%	Compatible
Leviton	IllumaTech	IPE04-1LZ	300	-	Not Compatible
	Sureslide Decora	6674	600	10-100%	Compatible
	Trimatron	6602	600	10-100%	Compatible
Cooper	Aspire	9536	1,000	-	Not Compatible

\*Minimum 2 lamps

## DIMMER COMPATIBILITY

Model: 9A19DIM/xxx/GU24/RC

Brand	Series	Model	Load (W)	Dimming Range	Dimmability
Lutron	Maestro	MAELV-600	600	20-100%	Compatible*
	Nova	NTELV-600	600	10-100%	Compatible
	Diva	DV-600P	600	10-100%	Compatible
	Toggler	TG-600P	600	10-100%	Compatible
	Caseta	PD-5NE	250	20-100%	Compatible
	Skylark Contour	CTELV-303P	300	10-100%	Compatible
	Diva	DVELV-300P	300	10-100%	Compatible
	Skylark Contour	CTCL-153P	150	20-90%	Compatible
	Diva	DVCL-153P	150	20-100%	Compatible
	Maestro C•L	MACL-153M	150	20-100%	Compatible
Leviton	IllumaTech	IPE04-1LZ	300	20-100%	Compatible
	Sureslide Decora	6674	600	20-100%	Compatible
	Trimatron	6602	600	-	Not Compatible
Cooper	Aspire	9536	1,000	-	Not Compatible

\*Maximum 4 lamps



# HIGH CRI A LAMP Family

## DIMMER COMPATIBILITY

Model: 11A19DIM/xxx/R

Brand	Series	Model	Load (W)	Dimming Range	Dimmability
Lutron	Maestro	MAELV-600	600	20-100%	Compatible*
	Nova	NTELV-600	600	10-100%	Compatible
	Diva	DV-600P	600	10-100%	Compatible
	Toggler	TG-600P	600	10-100%	Compatible
	Caseta	PD-5NE	250	20-100%	Compatible**
	Skylark Contour	CTELV-303P	300	20-100%	Compatible
	Diva	DVELV-300P	300	10-100%	Compatible
	Skylark Contour	CTCL-153P	150	10-100%	Compatible
	Diva	DVCL-153P	150	10-100%	Compatible
	Maestro C•L	MACL-153M	150	10-100%	Compatible
Leviton	IlumaTech	IPE04-1LZ	300	-	Not Compatible
	Sureslide Decora	6674	600	10-100%	Compatible
	Trimatron	6602	600	10-100%	Compatible
Cooper	Aspire	9536	1,000	-	Not Compatible

\*Maximum 1 lamp

\*\*Minimum 2 lamps

## DIMMER COMPATIBILITY

Model: 15A21DIM/xxx/N

Brand	Series	Model	Load (W)	Dimming Range	Dimmability
Lutron	Diva	DV-600P	600	0-100%	Compatible
	Toggler	TG-600P	600	-	Not Compatible
	Skylark Contour	CTCL-153P	150	0-100%	Compatible
	Toggler	TGCL-153P	150	0-100%	Compatible
	Diva	DVCL-153P	150	0-100%	Compatible
	Maestro C•L	MACL-153M	150	-	Not Compatible
	Ariadni	AYCL-153P	150	0-100%	Compatible
Leviton	Sureslide Decora	6674	600	0-100%	Compatible
	Trimatron	6602	600	-	Not Compatible
Cooper	Aspire	9534	600	-	Not Compatible

GREEN CREATIVE has provided this dimmer switch compatibility chart for guidance when selecting a dimmer and lamp combination. Our lamps were tested for compatibility with the above listed dimmers. Dimmers that do not appear on the chart might still be compatible but have not been tested. All testing has been performed with a stable main supply. The quality of the local main, existing installation and wiring, as well as different manufacturer versions of the above dimmers may affect dimming performance. Since no assurance can be provided regarding these factors, it is a general recommendation to perform a test on-site prior to installing the LED lamps.