# **DesignLights Consortium**





Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	150.9 W
Reported Light Output	21506 lm
Reported CCT	3000 K
Reported CRI (Ra)	83
Product ID	S-6S9MTH
DLC Family Code	EEEHFN
Listing Status	Listed
Date Qualified	2023-06-27

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-6S9MTH
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTBO11XX
Parent	No
Classification	Premium
DLC Family Code	EEEHFN
Input Power Type	AC

#### PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires	
General Application	High-Bay	
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings	

#### **PRODUCT CAPABILITIES VIEW DETAILS**

Integral Controls	Yes
····- 9· ··· - ···	

Dimming Capability and Range	Continuous Dimming to 10% or below		
Integral Control Capability	No Control Capability		
Sensor Type	Sensor Receptacle,Occupancy Sensing		
SSL V5 Wired Communication Protocol	0-10V Analog		
SSL V5 Wireless Communication Protocol	No Wireless Protocol		
Field Adjustable Light Output	Yes		
White-Tunable	Yes		
Warm-Dimming	No		
Field Adjustable Light Distribution	No		

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	21506 lm
Reported Efficacy (AC)	142.5 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	83
Reported R9	10
Reported IES Rf	83
Reported IES Rg	99
Reported IES Rcs,h1	-11
Reported Minimum Light Output	14254 lm
Reported Maximum Light Output	21506 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	21506 lm

# REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	150.9 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	100 W
Reported Maximum Input Wattage	150.9
Reported Default Input Wattage	150.9 W
Voltage Range	120-277 V

## **VERSION HISTORY VIEW DETAILS**

2023-06-27	Listed	5.1	Premium