

Project Name:	Type:
Part Number:	Date:



GREENCREATIVE

VALUE SELECT PAR FAMILY

FEATURES

- Suitable to replace 50W, 60W, 75W, 120W halogen
- Smooth dimming with existing dimmers*
- Compact size 1:1 halogen form factor
- Narrow & flood beam angles
- Suitable for use in wet locations**
- Operating temperature: -4°F / -20°C to +95°F / +35°C
- Rated Lifetime (L70): 25,000hrs
- 3 years limited warranty



110222

SPECIFICATIONS

Product	Model	Equiv.	Wattage (W)	CCT	Lumens	Efficacy (LPW)	Input Voltage	Beam Angle	CBCP (cd)	CRI	Dim.*	Power Factor	Base	Fixture Rating	ES
36212	6PAR16DIM/827FL35/RC	60W	6	2700K	550	92	120V	35°	1,000	82	Yes	0.7	E26	Enclosed	✓
36213	6PAR16DIM/830FL35/RC	60W	6	3000K	570	95	120V	35°	1,050	82	Yes	0.7	E26	Enclosed	✓
57991	6PAR16DIM/830FL35/R	60W	6	3000K	500	83	120V	35°	1,050	82	Yes	0.9	E26	Enclosed	✓
34933	5.5PAR20DIM/830NF25/N	50W	5.5	3000K	525	95	120V	25°	1180	82	Yes	0.7	E26	Non-Enclosed	✓
34934	5.5PAR20DIM/830FL40/N	50W	5.5	3000K	525	95	120V	40°	595	82	Yes	0.7	E26	Non-Enclosed	✓
34935	5.5PAR20DIM/840NF25/N	50W	5.5	4000K	525	95	120V	25°	1180	82	Yes	0.7	E26	Non-Enclosed	✓
34936	5.5PAR20DIM/840FL40/N	50W	5.5	4000K	525	95	120V	40°	595	82	Yes	0.7	E26	Non-Enclosed	✓
34937	10PAR30DIM/830NF25/N	75W	10	3000K	950	95	120V	25°	2910	82	Yes	0.7	E26	Non-Enclosed	✓
34938	10PAR30DIM/830FL40/N	75W	10	3000K	950	95	120V	40°	1315	82	Yes	0.7	E26	Non-Enclosed	✓
34939	10PAR30DIM/840NF25/N	75W	10	4000K	950	95	120V	25°	2910	82	Yes	0.7	E26	Non-Enclosed	✓
34940	10PAR30DIM/840FL40/N	75W	10	4000K	950	95	120V	40°	1315	82	Yes	0.7	E26	Non-Enclosed	✓
34941	10PAR30SNDIM/830NF25/N	75W	10	3000K	950	95	120V	25°	2910	82	Yes	0.7	E26	Non-Enclosed	✓
34942	10PAR30SNDIM/830FL40/N	75W	10	3000K	950	95	120V	40°	1315	82	Yes	0.7	E26	Non-Enclosed	✓
34943	10PAR30SNDIM/840NF25/N	75W	10	4000K	950	95	120V	25°	2910	82	Yes	0.7	E26	Non-Enclosed	✓
34944	10PAR30SNDIM/840FL40/N	75W	10	4000K	950	95	120V	40°	1315	82	Yes	0.7	E26	Non-Enclosed	✓
34945	13.5PAR38DIM/830NF25/N	120W	13.5	3000K	1280	95	120V	25°	5385	82	Yes	0.7	E26	Non-Enclosed	✓
34946	12PAR38DIM/830FL40/N	120W	12	3000K	1150	95	120V	40°	2235	82	Yes	0.7	E26	Non-Enclosed	✓
34947	13.5PAR38DIM/840NF25/N	120W	13.5	4000K	1280	95	120V	25°	5385	82	Yes	0.7	E26	Non-Enclosed	✓
34948	12PAR38DIM/840FL40/N	120W	12	4000K	1150	95	120V	40°	2235	82	Yes	0.7	E26	Non-Enclosed	✓


* This lamp might not be compatible with all dimmers. Please visit www.greencreative.com for compatibility information.

** For PAR16 lamps, they are suitable for use in damp locations.




VALUE SELECT PAR FAMILY


DIMENSIONS & WEIGHT




Model	Base	Dia.	MOL	Weight
6PAR16DIM/827FL35/RC	E26	1-15/16"	2-15/16"	0.09lb
6PAR16DIM/830FL35/RC				




Model	Base	Dia.	MOL	Weight
6PAR16DIM/830FL35/R	E26	1-15/16"	2-13/16"	0.1lb




Model	Base	MOL	Dia.	Weight
5.5PAR20DIM/830NF25/N	E26	3-3/16"	2-1/2"	0.09lb
5.5PAR20DIM/830FL40/N	E26	3-3/16"	2-1/2"	0.09lb
5.5PAR20DIM/840NF25/N	E26	3-3/16"	2-1/2"	0.09lb
5.5PAR20DIM/840FL40/N	E26	3-3/16"	2-1/2"	0.09lb



Model	Base	MOL	Dia.	Weight
10PAR30DIM/830NF25/N	E26	4-3/8"	3-3/4"	0.26lb
10PAR30DIM/830FL40/N	E26	4-3/8"	3-3/4"	0.21lb
10PAR30DIM/840NF25/N	E26	4-3/8"	3-3/4"	0.26lb
10PAR30DIM/840FL40/N	E26	4-3/8"	3-3/4"	0.21lb



Model	Base	MOL	Dia.	Weight
10PAR30SNDIM/830NF25/N	E26	3-3/8"	3-3/4"	0.26lb
10PAR30SNDIM/830FL40/N	E26	3-3/8"	3-3/4"	0.21lb
10PAR30SNDIM/840NF25/N	E26	3-3/8"	3-3/4"	0.26lb
10PAR30SNDIM/840FL40/N	E26	3-3/8"	3-3/4"	0.21lb



Model	Base	MOL	Dia.	Weight
13.5PAR38DIM/830NF25/N	E26	5-1/8"	4-3/4"	0.39lb
12PAR38DIM/830FL40/N	E26	5-1/8"	4-3/4"	0.32lb
13.5PAR38DIM/840NF25/N	E26	5-1/8"	4-3/4"	0.39lb
12PAR38DIM/840FL40/N	E26	5-1/8"	4-3/4"	0.32lb



VALUE SELECT PAR FAMILY

ORDERING INFORMATION

Model	Master Carton			Shipping Carton		
	Case Qty	Case Dimensions (LxWxH)	Case Weight	Case Qty	Case Dimensions (LxWxH)	Case Weight
6PAR16DIM/xxxxyyy/RC	12PCS	8-7/8" x 6-11/16" x 3-11/16"	1.6 lb	48PCS	13-3/4" x 9-3/8" x 8-1/4"	7.1 lb
6PAR16DIM/xxxxyyy/R	12PCS	8-3/8" x 6-11/16" x 3-11/16"	1.9 lb	48PCS	13-7/8" x 9-1/4" x 4-3/4"	8.32 lb
5.5PAR20DIM/xxxxyyy/N	6PCS	8-1/2"x5-3/4"x4-5/16"	1.17 lb	24PCS	12"x9-1/16"x9-7/16"	6.27 lb
10PAR30DIM/xxxxyyy/N	6PCS	12-3/8"x5-1/2"x8-3/8"	2.8 lb	24PCS	17-1/8"x12-13/16"x11-13/16"	13.91 lb
10PAR30SNDIM/xxxxyyy/N	6PCS	12-3/8"x4-1/2"x8-3/8"	2.25 lb	24PCS	17-1/8"x12-13/16"x9-5/8"	13.43 lb
13.5PAR38DIM/xxxxyyy/N	6PCS	15-1/4"X10-7/16"x6-1/2"	3.61 lb	24PCS	21-1/16"x15-3/4"x13-9/16"	19.62 lb
12PAR38DIM/xxxxyyy/N	6PCS	15-1/4"X10-7/16"x6-1/2"	3.61 lb	24PCS	21-1/16"x15-3/4"x13-9/16"	19.62 lb

Where xxx means 824-965 which indicates CRI and color temperature

Where yyyy means beam angle

CERTIFICATION INFORMATION


Product	Model	ES ID#
36212	6PAR16DIM/827FL35/RC	2388065
36213	6PAR16DIM/830FL35/RC	2388067
57991	6PAR16DIM/830FL35/R	2388067
34933	5.5PAR20DIM/830NF25/N	2347051
34934	5.5PAR20DIM/830FL40/N	2347061
34935	5.5PAR20DIM/840NF25/N	2347052
34936	5.5PAR20DIM/840FL40/N	2347062
34937	10PAR30DIM/830NF25/N	2347063
34938	10PAR30DIM/830FL40/N	2347065
34939	10PAR30DIM/840NF25/N	2347064
34940	10PAR30DIM/840FL40/N	2347066
34941	10PAR30SNDIM/830NF25/N	2347053
34942	10PAR30SNDIM/830FL40/N	2347059
34943	10PAR30SNDIM/840NF25/N	2347054
34944	10PAR30SNDIM/840FL40/N	2347060
34945	13.5PAR38DIM/830NF25/N	2347057
34946	12PAR38DIM/830FL40/N	2347055
34947	13.5PAR38DIM/840NF25/N	2347058
34948	12PAR38DIM/840FL40/N	2347056



VALUE SELECT PAR FAMILY


ILLUMINANCE & CANDELA DISTRIBUTION

5.5PAR20DIM/830NF25/N




Diameter	Footcandles
1.3	131
2.7	33
4.0	15
5.3	8
6.7	5


5.5PAR20DIM/830FL40/N



Diameter	Footcandles
2.2	66
4.4	17
6.6	7
8.7	4
10.9	3




Degree	Candela
0	1180
5	1088
15	511
25	188
35	83
45	31




Degree	Candela
0	595
5	339
15	249
25	104
35	48
45	24

6PAR16DIM/827/FL35/RC




Diameter	Footcandles
1.3	86
2.7	21
4.0	10
5.3	5
6.7	3


6PAR16DIM/827/FL35/R



Diameter	Footcandles
1.9	111
3.8	28
5.7	12
7.6	7
9.5	4



Degree	Candela
0	1011
5	952
15	649
25	288
35	132
45	59




Degree	Candela
0	1000
5	978
15	371
25	156
35	70
45	30



VALUE SELECT PAR FAMILY


ILLUMINANCE & CANDELA DISTRIBUTION

10PAR30DIM/830NF25/N




Diameter	Footcandles
1.3	323
2.7	81
4.0	36
5.3	20
6.7	13


10PAR30DIM/830FL40/N



Diameter	Footcandles
2.2	146
4.4	37
6.6	16
8.7	9
10.9	6




Degree	Candela
0	2910
5	2857
15	1908
25	920
35	429
45	175




Degree	Candela
0	1315
5	1227
15	395
25	162
35	72
45	35

10PAR30SDIM/830NF25/N




Diameter	Footcandles
1.3	323
2.7	81
4.0	36
5.3	20
6.7	13


10PAR30SDIM/830FL40/N



Diameter	Footcandles
2.2	146
4.4	37
6.6	16
8.7	9
10.9	6



Degree	Candela
0	2910
5	2857
15	1908
25	920
35	429
45	175




Degree	Candela
0	1315
5	1227
15	395
25	162
35	72
45	35



VALUE SELECT PAR FAMILY


ILLUMINANCE & CANDELA DISTRIBUTION

13.5PAR38DIM/830NF25/N




Diameter	Footcandles
1.3	598
2.7	150
4.0	66
5.3	37
6.7	24


12PAR38DIM/830FL40/N



Diameter	Footcandles
2.2	248
4.4	62
6.6	28
8.7	16
10.9	10



Degree	Candela
0	5385
5	4920
15	1450
25	465
35	214
45	76



Degree	Candela
0	2235
5	2240
15	1514
25	547
35	202
45	50

For other CCT use the following multiplier: 4000K 1.00

Note: All rights reserved. All sizes and specifications are subject to change at any time without notice.