



# LED VINTAGE CHANDELIER BULB

Add an elegant, timeless look to any room with the warm glow of these decorative flame tip LED vintage candelabra bulbs.

## FEATURES

- Energy efficient replacement for 25W, 40W or 60W incandescent replica
- High color rendering index (CRI) of 92 makes color appear more accurate
- Clear glass lens shows off vertical LED filaments
- Frosted glass lens diffuses light and reduces glare
- Candelabra (E12) base or standard household medium (E26) base
- Dimmable; see dimmer compatibility sheet for a full list of dimmers


## LISTINGS

- UL Listed for wet locations
- FCC
- RoHS
- DOE
- Rated for use in enclosed fixtures

## WARRANTY

- 1-year limited warranty; see [pltsolutions.com](http://pltsolutions.com) for warranty details

project name	type
catalog number	
comments	voltage
approved by	date



## APPLICATIONS

- Chandeliers
- Wall Sconces
- Decorative Fixtures

PERFORMANCE	Power Consumption	3, 3.5, 5.5 Watt
	Lumens	250, 300, 500
	Efficacy (LPW)	83, 86, 91
	CRI	92
	Beam Angle	330
	CCT	2400K
ELECTRICAL	LED L70 Life Hours	15,000
	Input Voltage	120V
CONSTRUCTION	Shape	B11
	Filament Type	Vertical
	Base	E12, E26
	Finish	Clear, Frosted
LISTINGS	Certifications	UL Listed; FCC; DOE
	Material Usage	RoHS – No mercury or lead
	Environment	Wet Location Rated; Enclosed Fixture Rated


# PERFORMANCE SUMMARY

Item #	Shape	Lumens	Wattage	LPW	Voltage	Replaces	CCT	CRI	Finish	Base	LED L70 Life Hours	Dimmable
PLT-12810	B11	250	3	83	120V	25W Incan.	2400K	92	Clear	E12	15,000	Yes
PLT-12811	B11	250	3	83	120V	25W Incan.	2400K	92	Frosted	E12	15,000	Yes
PLT-12812	B11	250	3	83	120V	25W Incan.	2400K	92	Clear	E26	15,000	Yes
PLT-12813	B11	250	3	83	120V	25W Incan.	2400K	92	Frosted	E26	15,000	Yes
PLT-12814	B11	300	3.5	86	120V	40W Incan.	2400K	92	Clear	E12	15,000	Yes
PLT-12815	B11	300	3.5	86	120V	40W Incan.	2400K	92	Frosted	E12	15,000	Yes
PLT-12816	B11	300	3.5	86	120V	40W Incan.	2400K	92	Clear	E26	15,000	Yes
PLT-12817	B11	300	3.5	86	120V	40W Incan.	2400K	92	Frosted	E26	15,000	Yes
PLT-12818	B11	500	5.5	91	120V	60W Incan.	2400K	92	Clear	E12	15,000	Yes
PLT-12819	B11	500	5.5	91	120V	60W Incan.	2400K	92	Frosted	E12	15,000	Yes
PLT-12820	B11	500	5.5	91	120V	60W Incan.	2400K	92	Clear	E26	15,000	Yes
PLT-12821	B11	500	5.5	91	120V	60W Incan.	2400K	92	Frosted	E26	15,000	Yes

# COMPATIBLE DIMMERS

Brand	Model	Compatible
LUTRON	PD-6WCL-WH-P	OK
LEGRAND	RHCL453PW	OK
LUTRON	DVCL-153PR-X	OK
LUTRON	CTCL-153PDH-X	OK
LEVITON	IPL06 R50-IPL06-10M	OK
LUTRON	DVELV-300P-X	OK
LUTRON	NLV-1000-X	X
LUTRON	SLV-600P-X	OK
LUTRON	RRD-6CL-X	OK
WATTSTOPPER	DCD267-W	OK
LEVITON	DW6HD-1BZ	X
LUTRON	P-PKG1W-WH	OK
LEVITON	DSL06-001-1LZ	OK
LEVITON	IPL06-011-10Z	OK
LEVITON	06674-002-10W	X
LEVITON	RDL06-001-10Z	OK
LEVITON	DSE06-001-10Z	OK
LEVITON	DDMX1-011-BLZ	OK
EATON	SAL06P3	OK
LEVITON	6672	OK
LEVITON	IPL06	X
LEVITON	6674	OK
LUTRON	MACL-153M-X	OK
LUTRON	MACL-153MH-X	OK
LUTRON	TGCL-153P-X	OK
LUTRON	DVCL-153P-X	OK

## DIMENSIONS



### E12 BASE DIMENSIONS

Height – 4.25"

Diameter – 1.38"



### E26 BASE DIMENSIONS

Height – 4.21"

Diameter – 1.38"

## WARNINGS

- Only use this LED chandelier bulb with the dimmers listed in the compatibility list. Using this bulb with incompatible dimmers may cause performance issues including humming, buzzing, flickering, and poor dimming performance.