

# LED T8 BALLAST BYPASS: GLASS

#### DESCRIPTION

Eliminate ballast maintenance costs and compatibility issues by retrofitting existing fluorescent fixtures with these ballast bypass LED T8 tubes.

#### **FEATURES**

- Frosted glass lens reduces visual glare
- Instantaneous full light output upon power-up
- Operates directly off of line voltage, no ballast needed
- Suitable for use in totally enclosed fixtures
- Solid state replacement for 8 ft. F96T8 and F96T12 tubes with R17d High Output bases
- Delivers up to 138 Lumens per Watt for highly efficient performance
- Ballast must be removed, and fixture rewired for double-ended operation during installation; see installation instructions for more information
- Wattage and output vary depending on installation method, see Wattage Table for full breakdown

#### LISTINGS

- UL Listed for damp locations
- FCC
- RoHS

#### WARRANTY

3-year prorated warranty; see pltsolutions.com for warranty details

project name	type
catalog number	
comments	voltage
approved by	date









### **APPLICATIONS**

- Office Lighting
- High Bays
- Industrial Strips
- Warehouses
- Stairwells
- Cold Storage

PERFORMANCE	Power Consumption	40W		
	Lumens	5500		
	Efficacy (LPW)	138		
	CRI	80		
	Beam	210°		
	сст	4000K, 5000K, 6500K		
	LED L70 Life Hours	>50000		
ELECTRICAL	Power Factor	0.9		
	THD	25%		
	Input Voltage	120-277V		
	Operating Temperature	-4°F to 113°F (-20°C to 45°C)		
CONSTRUCTION	Base	R17d		
	Lens	Frosted		
	Certifications	UL Listed; FCC		
LISTINGS	Material Usage	RoHS - No mercury or lead		
	Environment	Suitable for Damp Locations		


### PERFORMANCE SUMMARY

Item #	Length	Lumens*	Watts*	LPW*	ССТ	CRI	Beam	Envelope	Base	L70 Life Hours
PLT-90362	8'	5500	40	138	4000K	80	200°	Glass	R17d	>50,000
PLT-90363	8'	5500	40	138	5000K	80	200°	Glass	R17d	>50,000
PLT-90364	8'	5500	40	138	6500K	80	200°	Glass	R17d	>50,000

### **WIRING DIAGRAM**


## R17d Base 8' Type B Non-Dimming –

Electronic Ballast, Shunted Lampholders, 1 Lamp




## <u> R17d Base 8' Type B Non-Dimming –</u>

Electronic Ballast, Shunted Lampholders, 2 Lamps




### R17d Base 8' Type B Non-Dimming –

Electronic Ballast, Non-Shunted Lampholders, 1 Lamp




### R17d Base 8' Type B Non-Dimming –

<u> Electronic Ballast, Non-Shunted Lampholders, 2 Lamps</u>



## <u>R17d Base 8' Type B Non-Dimming – Magnetic Ballast</u>



## DIMENSIONS

### **DIMENSIONS**

Length - 96"

Diameter – 1"

## WARNINGS

• Not for use with ballasts.