



LED VINTAGE CHANDELIER BULB

Add an elegant, timeless look to any room with the warm glow of these decorative straight tip LED vintage candelabra bulbs.

FEATURES

- Energy efficient replacement for 25W, 40W or 60W incandescent replica
- High color rendering index (CRI) of 92 makes color appear more accurate
- Clear glass lens shows off two vertical LED filaments
- Frosted glass lens diffuses light and reduces glare
- Candelabra (E12) base or standard household medium (E26) base
- Dimmable; see dimmer compatibility sheet for a full list of dimmers

LISTINGS

- UL Listed for wet locations
- RoHS
- FCC
- DOE
- Rated for use in enclosed fixtures

WARRANTY

- 1-year limited warranty; see pltsolutions.com for warranty details

project name	type
catalog number	
comments	voltage
approved by	date



APPLICATIONS

- Chandeliers
- Wall Sconces
- Decorative Fixtures

PERFORMANCE	Power Consumption	3, 3.5, 5.5 Watt
	Lumens	250, 300, 500
	Efficacy (LPW)	83, 86, 91
	CRI	92
	CCT	2400K
	LED L70 Life Hours	15,000
ELECTRICAL	Input Voltage	120V
	Shape	B11
CONSTRUCTION	Filament Type	Vertical
	Base	E12, E26
	Finish	Clear, Frosted
	Certifications	UL Listed; FCC; DOE
LISTINGS	Material Usage	RoHS – No mercury or lead
	Environment	Wet Location Rated; Enclosed Fixture Rated


PERFORMANCE SUMMARY

Item #	Shape	Lumens	Wattage	LPW	Voltage	Replaces	CCT	CRI	Finish	Base	LED L70 Life Hours	Dimmable
PLT-12798	B11	250	3	83	120V	25W Incan.	2400K	92	Clear	E12	15,000	Yes
PLT-12799	B11	250	3	83	120V	25W Incan.	2400K	92	Frosted	E12	15,000	Yes
PLT-12800	B11	250	3	83	120V	25W Incan.	2400K	92	Clear	E26	15,000	Yes
PLT-12801	B11	250	3	83	120V	25W Incan.	2400K	92	Frosted	E26	15,000	Yes
PLT-12802	B11	300	3.5	86	120V	40W Incan.	2400K	92	Clear	E12	15,000	Yes
PLT-12803	B11	300	3.5	86	120V	40W Incan.	2400K	92	Frosted	E12	15,000	Yes
PLT-12804	B11	300	3.5	86	120V	40W Incan.	2400K	92	Clear	E26	15,000	Yes
PLT-12805	B11	300	3.5	86	120V	40W Incan.	2400K	92	Frosted	E26	15,000	Yes
PLT-12806	B11	500	5.5	91	120V	60W Incan.	2400K	92	Clear	E12	15,000	Yes
PLT-12807	B11	500	5.5	91	120V	60W Incan.	2400K	92	Frosted	E12	15,000	Yes
PLT-12808	B11	500	5.5	91	120V	60W Incan.	2400K	92	Clear	E26	15,000	Yes
PLT-12809	B11	500	5.5	91	120V	60W Incan.	2400K	92	Frosted	E26	15,000	Yes

COMPATIBLE DIMMERS

Dimmer Model#	Result
LUTRON MACL-153M-WH	OK
LUTRON DVCL-153P-WH	OK
LUTRON PD-6WCL-WH-P	OK
OLEGRAND RHCL453PW	OK
LEVITON WHITE NO.6674 600W	OK
LEVITON LIGH ALMOND NO.6672 600W	OK
LUTRON MACL-153MH-WH	OK
LUTRON TGCL-153P-WH	OK
LUTRON DVCL-153PR-WH	OK
LUTRON CTCL-153PDH-WH	OK
EATON SAL06P3	OK
Werno - F7C059	OK
LUTRON P-PKG1W-WH	OK
LEVITON DSL06-001-1LZ	OK
LEVITON IPL06-011-10Z	OK
LEVITON RDL06-001-10Z	OK
LEVITON DSE06-001-10Z	OK
LEVITON DDMX1-011-BLZ	OK
LEVITON SLIDE DIMMER SURESLIDE	OK
LUTRON DIVA DVELV-300P-WH	OK
LUTRON SKYLARK SLV-600P-WH	OK
LUTRON RADIORA2 RRD-6CL-WH	OK
WATTSTOPPER MICO DETECTOR DCD267-W	OK
LEVITON SLIDE DIMMER	OK
LEVITON SLIDE DIMMER 3WAY	OK
LUTRON CASEFA WIRELESS	OK
LUTRON DIVA CL	OK
SMART DIMMER MASTER 300W	OK
LEVITON SLIDE NO.IPL06 R50-IPL06-10M	OK
GEN 2.0 DC CONTROL 120VAC 60Hz	OK


DIMENSIONS



E12 BASE DIMENSIONS

Height – 3.78"

Diameter – 1.38"



E26 BASE DIMENSIONS

Height – 3.62"

Diameter – 1.38"

WARNINGS

- Only use this LED chandelier bulb with the dimmers listed in the compatibility list. Using this bulb with incompatible dimmers may cause performance issues including humming, buzzing, flickering, and poor dimming performance.