



7W LED A15 3000K FILAMENT BASICS MILKY DIMMABLE Item #776642 Ordering Code LED7A15/30K/FIL/M/D/B UPC 739698819570

- "700 lumens of Soft White light
- Dimmable
- Rated for use in totally enclosed fixtures
- For damp location use



TECHNICAL SPECIFICATIONS

ltem # 776642	Watts 7	Bulb Type A15	Base E26	Volts 120	Finish/Description Milky	Beam Angle (°) 320°	Color Temperature (CCT) 3000K
Color Soft White Light	CRI 80	Lumens 700	CBCP N/A	Average Hours 10000	M.O.L. (inches) 3.26	M.O.D. (inches) 1.89	Incandescent Equivalent 60
Energy Star N	DLC N	Title 24 Compliant N	: Safety Rated UL	Safety Rating Typ DAMP	oeEnclosed Rated Y	Dimmable Y	Warranty 2

Order Multiple QTY

APPLICATION SUGGESTIONS



Amusement







Ceiling Fan

Pendant / Downlight Portable Wall Mount / Sconce



45 West Commercial Ave.

Dimmer Compatibility Guide Product Family Name: 776639 776640 776641 776642 m Numb LED7A15/27K/FIL/D/B LED7A15/30K/FIL/D/B LED7A15/27K/FIL/M/D/B LED7A15/30K/FIL/M/D/B rdering Code em Number: rdering Code Lamps per Dimmer Recommer Minimu Model Nu Manufactu erall Ra Notes Pro IllumaTech IPI06 Best Dims down to 1% Leviton SureSlide 6633-P Best Dims down to 1% PI06-1LZ Best 0 Dims down to 1% Toggler FG-600 Best Dims down to 1% GCL-600 ms down to 19 Bes Incandescent/Halogen (Triac/Pha Cut/Leading Edge Dimmers) ımea Lutron Diva DV-600 Best 1 6 Dims down to 1% -600 Best ms down to 1% MAW-600 Maestro Good 3 6 Dims down to 1% Dims down to 1% Dims down to 1% Titan D703-PW Good Legrand Harmony Good Dims down to 1% IllumaTech IPL06 Best Dims down to 1% 1 6 Sureslide 6674 Best 1 6 Dims down to 1% Leviton)ecora 672 Best 0 Dims down to 1% Decora Slid DSL06-1LZ Best 1 Dims down to 1% 6 CTCL-153 Bes ms down to 19 kylark Sunnata STCL - 153 Best 1 6 Dims down to 1% VCL-153P Bes Diva Maestro ms down to 19 CFL/LED Lutron Best Dims down to 1% 1 6 Skylark SCL-153P Best Dims down to 1% oggler Best 6 Radio RA RA2RR-6CL-PD Best 0 Dims down to 1% 6 larmony Best 6 Legrand Radiant HCL453P Best 0 Dims down to 1% Adorne Paddle ADPD453LM2 Best 1 6 Dims down to 1% VPE04 Best Dims down to 1% Vizia 6 Leviton IllumaTech IPE04 Dims down to 1%, not smooth dimming Good)ecora 615-Good Dims down to 1%, not smooth dimming Skylark Countour CTELV-303P Best Dims down to 1% 1 6 Electronic Low Voltage Bes /ELV-300 ms down to 19 Lutron Maestro MAELV-600 Best 1 6 Dims down to 1% ELVB-300 Bes ns down to 19 /IERTI VTEL-600M-W Best 1 6 Dims down to 1% Legrand cene Director SCELV Best 6 Dims down to 1% 1 VPM-06 /izia Good 6 Dims down to 1%, flickering at LE with 2 Leviton 6613-P Best 6 Lutron Maestro MALV-600 Not compatibl Not turn on with 1-6 1 6 Harmony DLV703-PW 2 6 Legrand DLV703-PV Titan Good Dims down to 1% Leviton Decora Digital (Bluetooth DDMX1-BLZ Best Dims down to 1% Leviton Decora Smart Z-Wave Technology DZ6HD Best 1 6 Dims down to 1% ecora Smart WiFi Technology Leviton DW1KD Best ims down to 1% Lutron Caseta Wireless smart dimmer Wi-Fi PD-10NXD Best 6 Dims down to 1% 1 Lutron GE Caseta Wireless smart dimmer Wi-Fi Z WAVE PD-6WCL ZW3005 Best Best Dims down to 1% Dims down to 1% dorne SofTap DTP703TU ms down to 5% Good Bad Flickering at HE with 1-6 Miro Decorator DRD4-W Legrand Harmony Adorne Whisper H703PTUT Bad flickering at LE with 3-Best 6 Dims down to 1% Adorne Touch ADTH700MMTUM2 Best 0 Jims down to 1% Decorator DAL06P-C2-K-L Good 6 Dims down to 1% 2 Cooper AL06P-W-Kms down to 1%

aximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacture

tMay experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they re initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating				
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.			
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.			
Good	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.			
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output.			
High End (H.E.) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.			
Low End (L.E.) Dead Travel	been miles now mach, in any, dead cave exists at the top and bottom or the diminer's range. Dead caver's when the single tail be indeed without an ething the light level.			

ntact Informatio Contact Information: Bulbrite Industries Inc. 145 West Commercial Avenue Moonachie, New Jersey 07074

02017 Bulbrite Industries Inc.

I Rights Reserved.