

DesignLights Consortium



Classification	Premium
Primary Use	1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	30 W
Reported Light Output	3840 lm
Reported CCT	3500 K
Reported CRI (Ra)	82
Product ID	S-4FTXNC
DLC Family Code	YYYYFII
Listing Status	Listed
Date Qualified	2022-07-07

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-4FTXNC
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTM61111
Parent	Yes
Classification	Premium
DLC Family Code	YYYYFII
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer
Primary Use Designation	1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Daylight Sensing, Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	3840 lm
Reported Efficacy (AC)	128 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	82
Reported R9	8
Reported IES Rf	80
Reported IES Rg	90
Reported IES Rcs,h1	-12
Reported Minimum Light Output	2760 lm
Reported Maximum Light Output	3900 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	3840 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	30 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	20
Reported Maximum Input Wattage	30
Reported Default Input Wattage	30
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	3931 lm
Tested Efficacy (AC)	129.51 lm/W

Tested CCT	3422 K
Tested CRI (Ra)	83
Tested R9	8
Tested IES Rf	83
Tested IES Rg	93
Tested IES Rcs,h1	-12 %
Tested Duv	0.0017

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	30.4 W
Tested Total Harmonic Distortion	11.2 %
Tested Power Factor	0.968

VERSION HISTORY VIEW DETAILS

2022-07-07	Listed	5.1	Premium
------------	--------	-----	---------