

LED WORK LIGHT STRINGER

DESCRIPTION

Quickly set up temporary lighting in work or construction areas with these LED work light stringers.

FEATURES

- 5 or 10 LED lamp heads spaced approximately 10' apart
- 50' stringers are connectable up to 6 sets; 100' stringers are connectable up to 3 sets
- 18/2 AWG power cord with 120V 2-prong plug
- Frosted lens diffuses the light for reduced glare
- Includes cover for plug

LISTINGS

- ETL Listed for wet locations
- IP65
- FCC
- RoHS
- IK08

PERFORMANCE

- CRI: >80
- CCT: 5000K
- LED L70 Life Hours @25°C: >54,000 hours

ELECTRICAL

- Power Factor: >0.9
- Input Voltage: 120V
- Wire Gauge: SJTW 18/2 AWG
- Surge Protection: 1kV

THERMAL

-40°F to 104°F (-40°C to 40°C) operating temperature

CONSTRUCTION

- Injection molded PC housing with yellow finish
- Frosted PC lens reduces glare while evenly distributing light output
- Metal hook with spring for easy installation

WARRANTY

5-year limited warranty; see pltsolutions.com for warranty details

project name	type
catalog number	
comments	voltage
approved by	date









APPLICATIONS

- New Construction or Renovation
- Maintenance or Storage Spaces
- Short-term Maintenance Projects
- Warehouses and Workshops
- Highway Toll Stations

PERFORMANCE SUMMARY

Item #	Watts	Total Lumens	LPW	CRI	ССТ	# of Lamp Heads	Lumens per Head	Lens	Voltage	Max # of Connections	Length
PLT-12838	65W	8000	123	80	5000K	5	1600	PC	120V	6 sets	50'
PLT-12839	130W	16,000	123	80	5000K	10	1600	PC	120V	3 sets	100'

DIMENSIONS

PLT-12838

Lamp Head Height - 3.44" Lamp Head Diameter - 3.91"

Cord Length: 50'

Lead Length w/ Plug: 9.58' Length Between Heads: 9.89"

Tail Length w/ Plug: 5.93'




PLT-12839

Lamp Head Height - 3.44" Lamp Head Diameter - 3.94"

Cord Length: 100'


Lead Length w/ Plug: 9.48' Length Between Heads: 9.84' Tail Length w/ Plug: 5.58"

Weight - 8.05 lbs



PHOTOMETRICS

<u>Single Lamp Head</u>



WARNING

- Do not submerge in water.
- For use only on CGFI protected circuits.
- Keep at least 16 feet away from pools and spas.