



High Temperature LED High Bay

DESCRIPTION

Providing one-for-one replacement of metal halide or fluorescent fixtures, this LED high bay features rotatable panels that allow you to direct the light output in the direction needed.

FEATURES

- Up to 162 LPW ultra-high efficiency delivers superior performance over older HID high bays
- LED panels rotate individually 135-degrees outwards
- Designed for high temperatures, operates up to 140-degrees
- Replaces up to a 1000W metal halide fixture or an 8-lamp fluorescent fixture
- 0-10V dimmable
- Optional motion sensor and remote control; see Accessories section for more information

LISTINGS

- UL rated for damp locations
- IP20
- DesignLights Consortium® 5.1 Premium - meets the requirements for the highest DLC qualification for efficacy and lumen maintenance

PERFORMANCE

- CRI: 80
- CCT: 5000K
- LED L70 Life Hours: 160,000
- Philips Lumileds SMD LEDs

THERMAL

- -40°F to 140°F (-40°C to 60°C) operating temperature

ELECTRICAL

- THD: ≤20%
- Power Factor: ≥0.9
- Input Voltage: 120-277V
- Surge Protection: 6kV
- Dimmable power supply (0-10V)

INSTALLATION

- Designed for suspended mounting with V-hooks and 3.28-foot chain included; see installation instructions for more information

CONSTRUCTION

- Aluminum iron housing with white finish
- Polycarbonate matte lens protects LEDs while evenly distributing light

Project name	Type
Catalog number	
Comments	Voltage
Approved by	Date



WARRANTY

- 5-year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Warehouses
- Manufacturing Plants
- Distribution Centers
- Grocery Stores
- Gymnasiums
- Indoor Recreational Facilities
- Cold Storage
- Big Box Retail
- Service Repair Centers

PERFORMANCE SUMMARY

Item #	Model	Watts	Lumens	LPW	CCT	CRI	Dimming	Voltage	Replaces	DLC #	DLC Level
PLT-12722	Linear	160	25,920	162	5000K	80	0-10V	120-277V	MH400	PLTSN4D11313	5.1 Premium
PLT-12723	Linear	215	34,615	161	5000K	80	0-10V	120-277V	MH1000	PLTSN4D21313	5.1 Premium
PLT-12724	Linear	320	50,560	158	5000K	80	0-10V	120-277V	MH1000	PLTSN4D31313	5.1 Premium

ACCESSORIES

SKU	Description
PLT-12844	High Bay Occupancy Sensor and Photocell - Microwave - White - Screw-in Connector - 12 Volt
PLT-13121	High Bay Occupancy Sensor and Photocell - Passive Infrared (PIR) - White - Screw-In Connector - 12 Volt
PLTS-12281	Motion Sensor Remote

DIMENSIONS


PLT-12722

Length: 18.11"

Height: 1.7"

Width: 11.81"

Weight - 6.17 lbs




PLT-12723

Length: 18.11"

Height: 1.7"

Width: 11.81"

Weight - 6.61 lbs



PLT-12724

Length: 23.03"

Height: 1.7"

Width: 11.81"


Weight - 8.37 lbs




PHOTOMETRICS

PLT-12722

Luminous Intensity Distribution Curve



PLT-12723



PLT-12724

Luminous Intensity Distribution Curve

