





PLT-12751 - 150/200/240W,
3500/4000/5000K, 277-480V, 1000W MH
Equal, Black Finish, Sensor Ready





DIMENSIONS

Pendent



Surface-mounted w/ PLTS-12378



ADVANTAGE

- UL cUL certificate.
- Lumileds or Samsung Chip, high CRI.
- Input voltage 277-480VAC.
- Output constant current lever can be adjusted through output cable with 0-10V.
- No UV or IR in the beam.
- Easy to install and operate.
- Energy saving, long lifespan.
- Light is soft and uniform, safe to eyes.
- Instant start, NO humming.
- Green and eco-friendly without mercury.

APPLICATION

- Warehouse, factory and workshops;
- Highway toll station and gas station;
- Exhibition hall;
- Gymnasium and supermarkets, etc.

SPECIFICATIONS

OPTICAL	Input Power (Tolerance : ±10%)	240W (wattage tunable 25%-100% or 240W/200W/150W)		
	Color Temperature	3500K	4000K	5000K
	Efficacy (Tolerance : -3%)	143LM/W	160LM/W	148LM/W
	Lumen (Tolerance : -10%)	34000LM	38000LM	35000LM
	CRI	>80		
	Color Consistency	<7 Steps (or <7 SDCM)		
	UGR	<28 (X=4H, Y=8H; S/H=1; Reflectances: 70%/50%/20%)		
	Diffuser Type	PC Lens		
	Beam Angle (50%) (Tolerance : ±15%)	90 Degree		
ELECTRICAL	Input Voltage and Frequency	277-480VAC, 50/60Hz		
	PF (Tolerance : -3%)	≥0.9		
	THD (Tolerance : +5%)	≤20%		
	Flicker Percent	<5%		
	Driver Brand	Fahold Driver (0-10V dimming)		
	Driver Model	K1-V240B-260C12		
	Driver Surge protection	L/N-PE: 6kV, L-N: 6kV		
	Dimming	0-10V dimming standard(off)		
	Optional Accessory	Motion Microwave Sensor ¹ , PIR Motion Sensor ² , Surge-protective Device ³ , Wire guard ⁴ , Reflector shield ⁵		
MATERIALS	LED Brand	Lumileds		
	LED Type	SMD2835		
	LED QTY	400*2PCS		
	Housing	Die-cast aluminum		
	Housing Color	White*, Black, or Customized**		
	Waterproof Rating	WET (IP65)		
OTHERS	Operating Temperature	Without Motion Sensor: -40°C TO 50°C		
		With Motion Sensor: -30°C TO 50°C		
	Storage Temperature	-40°C TO 80°C		
	Operating Humidity	20% - 90% RH		
	Storage Humidity	10% - 95% RH		
Warranty	5 years			

*White Finish - PLT-12750

**Custom finish options available via Special Order. Call 1-800-624-4488.

PACKAGE

Lamp Type	Carton Size	Qty / Carton	Net Weight / Carton	Gross Weight / Carton
Pendent	330*330*145MM[11.61*11.61*5.71inch]	1PCS	2.7KG[5.95LBS]	3.2KG[7.05LBS]
Surface-mounted	330*330*145MM[11.61*11.61*5.71inch]	1PCS	3.1KG[6.83LBS]	3.6KG[7.94LBS]

Tolerance of Carton Size: ±15 MM[±0.59inch], Tolerance of Weight: ±10%.

Optional Accessories:

¹Motion Microwave Sensor - NPS-00041


²Motion PIR Sensor - NPS-00042

³Surge-protective Device - NPS-00029

⁴Wire Guard - NPS-00169

⁵Reflector Shield - NPS-00170

Special order items. Please call
1-800-624-4488 for more information.





NOTICE FOR USER

- Please turn off power before installation or maintenance.
- Verify that supply voltage is correct by comparing it with the luminaire label information. Please make sure the wiring is insulated.
- Installation, service, and maintenance of luminaries should be performed by a qualified licensed electrician.

TROUBLESHOOTING

Problem	Solution
Flickering Light	Turn off the power, then turn on again after 3 minutes. If the light continues to flicker, call a licensed electrician.
Fixture not turning on	Check the electrical connection.