





**PLT-12748** - 100/120/150W,  
3500/4000/5000K,  
277-480V, 400W MH Equal,  
White Finish, Sensor Ready





## DIMENSIONS

### Pendent



### Surface-mounted w/ PLTS-12377



## ADVANTAGE

- UL cUL certificate.
- Lumileds or Samsung Chip, high CRI.
- Input voltage 277-480VAC.
- Output constant current lever can be adjusted through output cable with 0-10V.
- No UV or IR in the beam.
- Easy to install and operate.
- Energy saving, long lifespan.
- Light is soft and uniform, safe to eyes.
- Instant start, NO humming.
- Green and eco-friendly without mercury.

## APPLICATION

- Warehouse, factory and workshops;
- Highway toll station and gas station;
- Exhibition hall;
- Gymnasium and supermarkets, etc.

## SPECIFICATIONS

<b>OPTICAL</b>	Input Power (Tolerance : ±10%)**	150W (wattage tunable 25%-100% or 150W/120W/100W)		
	Color Temperature	3500K	4000K	5000K
	Efficacy (Tolerance : -3%)**	143LM/W	160LM/W	148LM/W
	Lumen (Tolerance : -10%)**	21000LM	24000LM	22000LM
	CRI	>80		
	Color Consistency	<7 Steps (or <7 SDCM)		
	UGR	<28 (X=4H, Y=8H; S/H=1; Reflectances: 70%/50%/20%)		
	Diffuser Type	PC Lens		
	Beam Angle (50%) (Tolerance : ±15%)	90 Degree		
<b>ELECTRICAL</b>	Input Voltage and Frequency	277-480VAC, 50/60Hz		
	PF (Tolerance : -3%)	≥0.9		
	THD (Tolerance : +5%)	≤20%		
	Flicker Percent	<5%		
	Driver Brand	Fahold Driver (0-10V dimming )		
	Driver Model	K1-V150B-260C12		
	Driver Surge protection	L/N-PE: 6kV, L-N: 6kV		
	Dimming	0-10V dimming standard(off)		
	Optional Accessory	Motion Microwave Sensor <sup>1</sup> , PIR Motion Sensor <sup>2</sup> , Surge-protective Device <sup>3</sup> , Wire guard <sup>4</sup> , Reflector shield <sup>5</sup>		
<b>MATERIALS</b>	LED Brand	Lumileds		
	LED Type	SMD2835		
	LED QTY	240*2PCS		
	Housing	Die-cast aluminum		
	Housing Color	White, Black*, or Customized**		
	Waterproof Rating	WET (IP65)		
<b>OTHERS</b>	Operating Temperature	Without Motion Sensor: -40°C TO 50°C With Motion Sensor: -30°C TO 50°C		
	Storage Temperature	-40°C TO 80°C		
	Operating Humidity	20% - 90% RH		
	Storage Humidity	10% - 95% RH		
	Warranty	5 years		

*\*Black Finish - PLT-12749*

*\*\*Custom finish options available via Special Order. Call 1-800-624-4488.*

## PACKAGE

Lamp Type	Carton Size	Qty / Carton	Net Weight / Carton	Gross Weight / Carton
Pendent	295*295*135MM[11.61*11.61*5.31inch]	1PCS	2.1KG[4.63LBS]	2.5KG[5.51LBS]
Surface-mounted	295*295*135MM[11.61*11.61*5.31inch]	1PCS	2.5KG[5.51LBS]	2.9KG[6.39LBS]

Tolerance of Carton Size: ±15 MM, Tolerance of Weight: ±10%.

### Optional Accessories:

<sup>1</sup>Motion Microwave Sensor - NPS-00041


<sup>2</sup>Motion PIR Sensor - NPS-00042

<sup>3</sup>Surge-protective Device - NPS-00029

<sup>4</sup>Wire Guard - NPS-00169

<sup>5</sup>Reflector Shield - NPS-00170

*Special order items. Please call  
1-800-624-4488 for more information.*





## NOTICE FOR USER

- Please turn off power before installation or maintenance.
- Verify that supply voltage is correct by comparing it with the luminaire label information. Please make sure the wiring is insulated.
- Installation, service, and maintenance of luminaries should be performed by a qualified licensed electrician.

## TROUBLESHOOTING

Problem	Solution
Flickering Light	Turn off the power, then turn on again after 3 minutes. If the light continues to flicker, call a licensed electrician.
Fixture not turning on	Check the electrical connection.