

plano **ARCH**

LSMT | eCrescent

Product Data Sheet



COMMERCIAL-GRADE

Surface Mount Disk Downlight



CCTselect



TruColor Rendering

4" | 6"

Product Overview

The LSMT eCrescent-Series is built for 5-way switchable CCT and is suitable for use in dry and damp locations, perfect for use in kitchens, hallways, stairways, bathrooms, closets, and just about anywhere you'd need it.

Featuring a non-compromise 5-year warranty, Energy Star and JA8-compliant, the SlimDisk is a clean and modern solution for surface mounted driverless design.

ARCHIPELAGO luminaires and LED components has been tested by independent laboratory in accordance to IESNA LM79 and LM80. LED color temperature is warranted to shift no more than 180K over the standard warranty period. Furthermore, the range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Product Warranty*



5-Year Warranty



50,000 Hrs

* Standard warranty. Extended warranty available.

Applications



Residential



Hallway



Entryway



Retail

Main Features

- Low-Profile Back-Lit Design
- Durable Thermoplastic Housing w/ Frosted Lens
- For New Construction or Retrofit Applications
- Suitable for Indoor/Outdoor Use in Dry, Damp, & Wet Locations (IP65)
- Suitable for Use in Closets, In Accordance to NEC Guidelines
- Installs on Ceiling and Standard Junction Boxes
- Dimmable to 5% on Compatible TRIAC & ELV Dimmers
- 5-Year, 50,000Hr Warranty
- CEC T.20 & T.24 JA8 Compliant
- NEC Compliant, Suitable for Use in Closet
- Energy Star Certified



Project Details






Project Name:

Fixture Schedule:

Project Number:

Notes:

Highlights

Features	Description
5-CCTselect	 CCT selectable: 5-way dip-switch
90CRI+	 Title.24 Compliant. 90CRI+ TrueColor
Wet Listed	 Suitable for use in dry, damp, and wet locations
Versatile Applications	 Ready for direct install or retrofit ready (kits sold separately).
Limited Warranty	 5-Year Warranty

Key Specifications

- **LED Chip:** Samsung 2835, LM80, IP-Protected
- **Lightweight Frame:** 6063 Aluminum
- **Operating Temp:** -10°F — 125°F
- **IP:** IP65 Wet Locations
- **Dimming:** 120V TRIAC & ELV
- **Input Voltage:** 120V
- **PF:** >0.9 Non-Flicker
- **Efficacy:** ~67LM/W
- **THD:** <15%
- **CRI:** >90

Certifications



Model Specifications

Model	Size (in)	Watt	Lumen	CCTselect	CRI
LSMT4	4"	10W	600LM / 610LM / 600LM / 600LM / 610LM /	2700K / 3000K / 3500K / 4000K / 5000K /	90CRI+
LSMT6	6"	15W	910LM / 950LM / 900LM / 910LM / 1000LM /	2700K / 3000K / 3500K / 4000K / 5000K /	

Ordering Guide

Model Series	Size (FT)	Watt	CCTselect (K)	Sensor
LSMT LED Surface Mount Disk	4 4"	10 10W	-S5E CCTselect: 27 2700K 30 3000K 35 3500K 40 4000K 50 5000K	/P Built-In PIR
	6 6"	15 15W		

Ordering number example:

Choose your model specifications:

LSMT615-S5E/P	LSMT			-S5E	/P
Please place dashes (-) in correct order.	Model Series	Size	Watt	CCTselect	Sensor Option

Sizing & Measurements

Model Series	Dimensions	Overall Diameter (in)	Emitting Diameter (in)	Depth (IN)
LSMT4		5.98	4.03	0.95
LSMT6		7.32	5.28	0.95

Dimmer Compatibility List

Make	Model	Min Output (mA)	Max Output (mA)	Min Dimming	Max Dimming
LEVITON	ELECT/V/ART 40201	30	280	10%	98%
	6674	10	268	3%	93%
	6633-P	1	285	0%	99%
	6613	9	284	3%	99%
	66EV	59	284	21%	99%
	DDE06	9	266	3%	93%
LUTRON	DVCL-153P	23	267	8%	93%
	CTCL-153P	16	267	6%	93%
	MACL-153M	18	260	6%	91%
	SCL-153P	5	268	2%	93%
	SELV-303P	19	271	7%	94%
	DVSCML-300P	18	268	6%	93%