

Features & Specifications



LED Strip Lights

INTENDED USE – LED strip light fixtures can be used for warehouses, indoor storage facilities and office buildings. These LED fixtures will yield a significant reduction in energy consumption compared to standard fluorescent fixtures and virtually eliminate ongoing maintenance expenses with a long-lasting lifespan. Designed for use in damp locations, the LED strip light fixture will provide a brighter light output to utility areas and stairwells.

CONSTRUCTION – Heavy-duty die cast aluminum housing with white polyester powder paint for corrosion-free durability. Resistant to rough vibrations and external impacts. Heavy duty frosted lens protects the LEDs and provides even light distribution.


OPTICS – High-performance LEDs maintain a 11,790 Lumen output at 5000K for 50,000 hours of use. ≥80 CRI. PMMA lens.

ELECTRICAL – Input voltage of 120-277 VAC, 50/60Hz. Built-in 2kV surge protection.

INSTALLATION - Features two metal buckle plates that snap-on to the strip light fixture for surface mounting. Dimmable down to 10% using a 0-10V driver.

LISTINGS – UL Certified to safety standards for damp locations. Rated for -45°C to 45°C ambient temperature. DLC 5.1 Standard - PLTM385132

WARRANTY – 5-year warranty. PLT products that are damaged or defective will be repaired or replaced at PLT's choosing for a period of 5 years. Contact 1-800-624-4488 for more information.



Dimensions:

Length: 94.2 in.
Width: 2.4 in.
Height: 2.8 in.



Compatible Dimmers

Brand	Model	Dim to off voltage
LUTRON	NTSTV-DV	0.527V
LUTRON	NFTV	0.515V
LUTRON	DVTV	0.765V
LEVITON	IP710	0.609V
LEVITON	DS710	0.578V
LEGRAND	RH4FBL3PW	0.568V

SKU #	Kelvin	Lumens	CRI	Wattage	Voltage	DLC	Mounting	Lens	Life Hours	Warranty
PLT-80038	5000K	11,790	80	90	120-277	Yes	Surface	PMMA	50,000	5 YEAR