# **DesignLights Consortium**





Classification	Standard
Primary Use	Direct Linear Ambient Luminaires
Reported Input Wattage	65 W
Reported Light Output	8580 lm
Reported CCT	5000 K
Reported CRI (Ra)	82
Product ID	S-26N93V
DLC Family Code	DDDKUI
Listing Status	Listed
Date Qualified	2024-01-26

### PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-26N93V
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTM2441321
Parent	Yes
Classification	Standard
DLC Family Code	DDDKUI
Length	4.0 ft
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires	
General Application	Linear Ambient	
Primary Use Designation	Direct Linear Ambient Luminaires	

### CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	8580 lm
Reported Efficacy (AC)	132 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	82
Reported R9	14
Reported IES Rf	80
Reported IES Rg	90
Reported IES Rcs,h1	-12
Reported Default Light Output	8580 lm

#### **REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS**

Reported Input Wattage	65 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.9
Reported Default Input Wattage	65 W
Voltage Range	120-277 V

#### TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
Tested Light Output	8418.16 lm
Tested Efficacy (AC)	133.89 lm/W

Tested CCT	4979 K
Tested CRI (Ra)	83.2
Tested R9	13
Tested IES Rf	83
Tested IES Rg	95
Tested IES Rcs,h1	13 %
Tested Duv	0.0011

## TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	62.87 W
Tested Total Harmonic Distortion	9.646 %
Tested Power Factor	0.9646

### VERSION HISTORY VIEW DETAILS

2024-01-26	Listed	5.1	Standard
------------	--------	-----	----------