

# DesignLights Consortium



Classification	Standard
Primary Use	Direct Linear Ambient Luminaires
Reported Input Wattage	34 W
Reported Light Output	4488 lm
Reported CCT	3500 K
Reported CRI (Ra)	82
Product ID	S-M4V2B8
DLC Family Code	<a href="#">QQQVXT</a>
Listing Status	Listed
Date Qualified	2022-12-21

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-M4V2B8
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTM946142
Parent	Yes
Classification	Standard
DLC Family Code	QQQVXT
Length	4.0 ft
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Linear Ambient
Primary Use Designation	Direct Linear Ambient Luminaires

## CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4488 lm
Reported Efficacy (AC)	132 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	82
Reported R9	7
Reported IES Rf	83
Reported IES Rg	98
Reported IES Rcs,h1	-12
Reported Minimum Light Output	4488 lm
Reported Maximum Light Output	4488 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	4488 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	34 W
Reported Total Harmonic Distortion	7.4 %
Reported Power Factor	0.995
Reported Minimum Input Wattage	34.0 W
Reported Maximum Input Wattage	34
Reported Default Input Wattage	34 W

Voltage Range	120-277 V
---------------	-----------

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
Tested Light Output	4459 lm
Tested Efficacy (AC)	128.46 lm/W
Tested CCT	3408 K
Tested CRI (Ra)	82
Tested R9	7
Tested IES Rf	83
Tested IES Rg	98
Tested IES Rcs,h1	-12 %
Tested Duv	-0.00077

## TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	34.7 W
Tested Total Harmonic Distortion	7.4 %
Tested Power Factor	0.952

## PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

SPDX File	<a href="#">Download File</a>
-----------	-------------------------------

## VERSION HISTORY VIEW DETAILS

2022-12-21	Listed	5.1	Standard
------------	--------	-----	----------