# **DesignLights Consortium**





| Classification         | Premium  |
|------------------------|--|
| Primary Use            | Low-Bay Luminaires for Commercial and Industrial Buildings |
| Reported Input Wattage | 65 W   |
| Reported Light Output  | 8515 lm  |
| Reported CCT           | 5000 K   |
| Reported CRI (Ra)      | 84   |
| Product ID             | S-0DNSP7   |
| DLC Family Code        | MMMSUM   |
| Listing Status         | Listed   |
| Date Qualified         | 2024-01-11   |

## **PRODUCT INFORMATION VIEW DETAILS**

| Qualified Product List         | Solid State Lighting                  |
|--------------------------------|---------------------------------------|
| Technical Requirements Version | 5.1                                   |
| Product ID                     | S-0DNSP7                              |
| Manufacturer                   | Precision Lighting & Transformer, Inc |
| Brand                          | PLT                                   |
| Model Number                   | PLTM151322                            |
| Parent                         | Yes                                   |
| Classification                 | Premium                               |
| DLC Family Code                | MMMSUM                                |
| Input Power Type               | AC                                    |

## **PRODUCT CATEGORIZATION VIEW DETAILS**

| Category                | Indoor Luminaires  |  |
|-------------------------|--|--|
| General Application     | Low-Bay  |  |
| Primary Use Designation | Low-Bay Luminaires for Commercial and Industrial Buildings |  |

## **CONTROL FEATURES VIEW DETAILS**

| ) |
|---|

| Dimming Capability and Range           | Continuous Dimming to 10% or below |
|--|------------------------------------|
| Integral Control Capability            | No Control Capability              |
| Sensor Type                            | No Sensor                          |
| SSL V5 Wired Communication Protocol    | 0-10V Analog                       |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol               |
| Field Adjustable Light Output          | No                                 |
| White-Tunable                          | No                                 |
| Warm-Dimming                           | No                                 |
| Field Adjustable Light Distribution    | No                                 |
|  |                                    |

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output         | 8515 lm  |
|-------------------------------|----------|
| Reported Efficacy (AC)        | 131 lm/W |
| Reported CCT                  | 5000 K   |
| Reported CRI (Ra)             | 84       |
| Reported R9                   | 11       |
| Reported IES Rf               | 84       |
| Reported IES Rg               | 95       |
| Reported IES Rcs,h1           | -12      |
| Reported Default Light Output | 8515 lm  |

#### REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage             | 65 W      |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 5.8 %     |
| Reported Power Factor              | 0.98      |
| Reported Default Input Wattage     | 65 W      |
| Voltage Range                      | 120-277 V |

### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

| Tested Voltage for Minimum Efficacy | 120         |
|-------------------------------------|-------------|
| Tested Light Output                 | 8520 lm     |
| Tested Efficacy (AC)                | 136.71 lm/W |
| Tested CCT                          | 5139 K      |
| Tested CRI (Ra)                     | 84          |
| Tested R9                           | 11          |
| Tested IES Rf                       | 84          |
| Tested IES Rg                       | 95          |

| Tested IES Rcs,h1 | -12 %  |
|-------------------|--------|
| Tested Duv        | 0.0023 |

#### **TESTED ELECTRICAL PERFORMANCE VIEW DETAILS**

| Tested Input Wattage             | 62.3 W |
|----------------------------------|--------|
| Tested Total Harmonic Distortion | 5.8 %  |
| Tested Power Factor              | 0.976  |

## PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

| SPDX File | Download File |
|-----------|---------------|
|-----------|---------------|

## **VERSION HISTORY VIEW DETAILS**

| 2023-03-06 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|
|            |        |     |         |