

DesignLights Consortium



| | |
|------------------------|-------------------------------------------------------------|
| Classification | Premium |
| Primary Use | High-Bay Luminaires for Commercial and Industrial Buildings |
| Reported Input Wattage | 105 W |
| Reported Light Output | 14280 lm |
| Reported CCT | 5000 K |
| Reported CRI (Ra) | 79 |
| Product ID | S-9D3IC6 |
| DLC Family Code | MMMTEA |
| Listing Status | Listed |
| Date Qualified | 2024-01-11 |

PRODUCT INFORMATION VIEW DETAILS

| | |
|--------------------------------|---------------------------------------|
| Qualified Product List | Solid State Lighting |
| Technical Requirements Version | 5.1 |
| Product ID | S-9D3IC6 |
| Manufacturer | Precision Lighting & Transformer, Inc |
| Brand | PLT |
| Model Number | PLTM15D322 |
| Parent | Yes |
| Classification | Premium |
| DLC Family Code | MMMTEA |
| Input Power Type | AC |

PRODUCT CATEGORIZATION VIEW DETAILS

| | |
|-------------------------|-------------------------------------------------------------|
| Category | Indoor Luminaires |
| General Application | High-Bay |
| Primary Use Designation | High-Bay Luminaires for Commercial and Industrial Buildings |

CONTROL FEATURES VIEW DETAILS

| | |
|-------------------|----|
| Integral Controls | No |
|-------------------|----|

| | |
|----------------------------------------|------------------------------------|
| Dimming Capability and Range | Continuous Dimming to 10% or below |
| Integral Control Capability | No Control Capability |
| Sensor Type | No Sensor |
| SSL V5 Wired Communication Protocol | 0-10V Analog |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol |
| Field Adjustable Light Output | No |
| White-Tunable | No |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | No |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| | |
|-------------------------------|----------|
| Reported Light Output | 14280 lm |
| Reported Efficacy (AC) | 136 lm/W |
| Reported CCT | 5000 K |
| Reported CRI (Ra) | 79 |
| Reported R9 | -11 |
| Reported IES Rf | 81 |
| Reported IES Rg | 94 |
| Reported IES Rcs,h1 | -15 |
| Reported Default Light Output | 14280 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| | |
|------------------------------------|-----------|
| Reported Input Wattage | 105 W |
| Reported Total Harmonic Distortion | 10.1 % |
| Reported Power Factor | 0.97 |
| Reported Default Input Wattage | 105 W |
| Voltage Range | 120-277 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| | |
|-------------------------------------|------------|
| Tested Voltage for Minimum Efficacy | 120 |
| Tested Light Output | 14529 lm |
| Tested Efficacy (AC) | 138.9 lm/W |
| Tested CCT | 4972 K |
| Tested CRI (Ra) | 79 |
| Tested R9 | -11 |
| Tested IES Rf | 81 |
| Tested IES Rg | 94 |

| | |
|-------------------|--------|
| Tested IES Rcs,h1 | -15 % |
| Tested Duv | 0.0027 |

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

| | |
|----------------------------------|---------|
| Tested Input Wattage | 104.6 W |
| Tested Total Harmonic Distortion | 10.1 % |
| Tested Power Factor | 0.971 |

PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

| | |
|-----------|-------------------------------|
| SPDX File | Download File |
|-----------|-------------------------------|

VERSION HISTORY VIEW DETAILS

| | | | |
|------------|--------|-----|---------|
| 2023-03-06 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|