

DesignLights Consortium



| | |
|------------------------|---|
| Classification | Premium |
| Primary Use | Architectural Flood and Spot Luminaires |
| Reported Input Wattage | 15.2 W |
| Reported Light Output | 2030 lm |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 84 |
| Product ID | S-UNLK2S |
| DLC Family Code | EMWAOO |
| Listing Status | Listed |
| Date Qualified | 2022-05-19 |

PRODUCT INFORMATION VIEW DETAILS

| | |
|--------------------------------|--|
| Qualified Product List | Solid State Lighting |
| Technical Requirements Version | 5.1 |
| Product ID | S-UNLK2S |
| Manufacturer | Precision Lighting & Transformer, Inc |
| Brand | PLT Solutions |
| Model Number | PLTSNH111Y5[1;2;Blank][1;Blank][1;3;2;4] |
| Parent | Yes |
| Classification | Premium |
| DLC Family Code | EMWAOO |
| Input Power Type | AC |

PRODUCT CATEGORIZATION VIEW DETAILS

| | |
|-------------------------|---|
| Category | Outdoor Luminaires |
| General Application | Low Output |
| Primary Use Designation | Architectural Flood and Spot Luminaires |

CONTROL FEATURES VIEW DETAILS

| | |
|-------------------|-----|
| Integral Controls | Yes |
|-------------------|-----|

| | |
|--|------------------------------------|
| Dimming Capability and Range | Continuous Dimming to 10% or below |
| Integral Control Capability | No Control Capability |
| Sensor Type | Exterior Photocell |
| SSL V5 Wired Communication Protocol | 0-10V Analog |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol |
| Field Adjustable Light Output | No |
| White-Tunable | Yes |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | Yes |
| Field Adjustable Distribution Type | Integral FALD |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| | |
|-------------------------------|-------------|
| Reported Light Output | 2030 lm |
| Reported Efficacy (AC) | 133.72 lm/W |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 84 |
| Reported R9 | 10 |
| Reported IES Rf | 85 |
| Reported IES Rg | 97 |
| Reported IES Rcs,h1 | -11 |
| Reported Minimum Light Output | 2006 lm |
| Reported Maximum Light Output | 2030 lm |
| Reported Minimum CCT | 3000 K |
| Reported Maximum CCT | 5000 K |
| Reported Default Light Output | 2030 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| | |
|------------------------------------|-----------|
| Reported Input Wattage | 15.2 W |
| Reported Total Harmonic Distortion | 15 % |
| Reported Power Factor | 0.9 |
| Reported Minimum Input Wattage | 15.0 W |
| Reported Maximum Input Wattage | 15.2 |
| Reported Default Input Wattage | 15 W |
| Voltage Range | 120-277 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| | |
|-------------------------------------|-----|
| Tested Voltage for Minimum Efficacy | 277 |
|-------------------------------------|-----|

| | |
|---|----------------|
| Tested Light Output | 2050 lm |
| Tested Efficacy (AC) | 131.4 lm/W |
| Tested CCT | 3041 K |
| Tested CRI (Ra) | 84 |
| Tested R9 | 10 |
| Tested IES Rf | 85 |
| Tested IES Rg | 97 |
| Tested IES Rcs,h1 | -11 % |
| Tested Duv | -0.0015 |
| Field Adjustable Light Distribution Setting | No restriction |

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

| | |
|----------------------------------|--------|
| Tested Input Wattage | 15.6 W |
| Tested Total Harmonic Distortion | 8.6 % |
| Tested Power Factor | 0.932 |

VERSION HISTORY VIEW DETAILS

| | | | |
|------------|--------|-----|---------|
| 2022-05-19 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|