DesignLights Consortium





Classification	Premium
Primary Use	Architectural Flood and Spot Luminaires
Reported Input Wattage	59.5 W
Reported Light Output	7782.2 lm
Reported CCT	3000 K
Reported CRI (Ra)	80
Product ID	S-9ZYH38
DLC Family Code	EMWAOP
Listing Status	Listed
Date Qualified	2022-05-19

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting				
Technical Requirements Version	5.1				
Product ID	S-9ZYH38				
Manufacturer	Precision Lighting & Transformer, Inc				
Brand	PLT Solutions				
Model Number	PLTSNH241Y5[1;2;Blank][1;Blank][1;3;2;4]				
Parent	No				
Classification	Premium				
DLC Family Code	EMWAOP				
Input Power Type	AC				

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires	
General Application	Mid Output	
Primary Use Designation	Architectural Flood and Spot Luminaires	

CONTROL FEATURES VIEW DETAILS

Integral Controls

Yes

DLC Qualified Product List - Solid State Lighting

Dimming Capability and Range	Continuous Dimming to 10% or below		
Integral Control Capability	No Control Capability		
Sensor Type	Exterior Photocell		
SSL V5 Wired Communication Protocol	0-10V Analog		
SSL V5 Wireless Communication Protocol	No Wireless Protocol		
Field Adjustable Light Output	No		
White-Tunable	Yes		
Warm-Dimming	No		
Field Adjustable Light Distribution	Yes		
Field Adjustable Distribution Type	Integral FALD		
Field Adjustable Distribution Type	Integral FALD		

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	7782.2 lm
Reported Efficacy (AC)	130.79 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	80
Reported R9	10
Reported IES Rf	84
Reported IES Rg	98
Reported IES Rcs,h1	-11
Reported Minimum Light Output	7782.2 lm
Reported Maximum Light Output	7782.2 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	7782.2 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	59.5 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	59.5 W
Reported Maximum Input Wattage	59.5
Reported Default Input Wattage	59.5 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Field Adjustable Light Distribution Setting Pointing Straight Down

VERSION HISTORY VIEW DETAILS

022-05-19	Listed	5.1	Premium