# **DesignLights Consortium**





| Classification         | Premium                                 |
|------------------------|---|
| Primary Use            | Architectural Flood and Spot Luminaires |
| Reported Input Wattage | 81.96 W                                 |
| Reported Light Output  | 10712.1 lm                              |
| Reported CCT           | 3000 K                                  |
| Reported CRI (Ra)      | 80                                      |
| Product ID             | S-U4DI0S                                |
| DLC Family Code        | EMWAOP                                  |
| Listing Status         | Listed                                  |
| Date Qualified         | 2022-05-19                              |

### PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List         | Solid State Lighting                     |  |  |
|--------------------------------|--|--|--|
| Technical Requirements Version | 5.1                                      |  |  |
| Product ID                     | S-U4DI0S                                 |  |  |
| Manufacturer                   | Precision Lighting & Transformer, Inc    |  |  |
| Brand                          | PLT Solutions                            |  |  |
| Model Number                   | PLTSNH251Y5[1;2;Blank][1;Blank][1;3;2;4] |  |  |
| Parent                         | No                                       |  |  |
| Classification                 | Premium                                  |  |  |
| DLC Family Code                | EMWAOP                                   |  |  |
| Input Power Type               | AC                                       |  |  |

## PRODUCT CATEGORIZATION VIEW DETAILS

| Category                | Outdoor Luminaires                      |  |
|-------------------------|---|--|
| General Application     | High Output                             |  |
| Primary Use Designation | Architectural Flood and Spot Luminaires |  |

## **CONTROL FEATURES VIEW DETAILS**

| Integral Controls | Yes |
|-------------------|-----|
|-------------------|-----|

| Dimming Capability and Range           | Continuous Dimming to 10% or below |
|--|------------------------------------|
| Integral Control Capability            | No Control Capability              |
| Sensor Type                            | Exterior Photocell                 |
| SSL V5 Wired Communication Protocol    | 0-10V Analog                       |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol               |
| Field Adjustable Light Output          | No                                 |
| White-Tunable                          | Yes                                |
| Warm-Dimming                           | No                                 |
| Field Adjustable Light Distribution    | Yes                                |
| Field Adjustable Distribution Type     | Integral FALD                      |

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output         | 10712.1 lm  |
|-------------------------------|-------------|
| Reported Efficacy (AC)        | 130.7 lm/W  |
| Reported CCT                  | 3000 K      |
| Reported CRI (Ra)             | 80          |
| Reported R9                   | 7           |
| Reported IES Rf               | 83          |
| Reported IES Rg               | 98          |
| Reported IES Rcs,h1           | -11         |
| Reported Minimum Light Output | 10455.93 lm |
| Reported Maximum Light Output | 10712.1 lm  |
| Reported Minimum CCT          | 3000 K      |
| Reported Maximum CCT          | 5000 K      |
| Reported Default Light Output | 10712.1 lm  |

### REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage             | 81.96 W   |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 15 %      |
| Reported Power Factor              | 0.9       |
| Reported Minimum Input Wattage     | 80 W      |
| Reported Maximum Input Wattage     | 81.96     |
| Reported Default Input Wattage     | 80 W      |
| Voltage Range                      | 120-277 V |

### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

| Field Adjustable Light Distribution Setting | Pointing Straight Down |
|---|------------------------|

# **VERSION HISTORY VIEW DETAILS**

| 2022-05-19 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|
|            |        |     |         |