



REFINE PAR WITH SWAPPABLE LENS

MODEL

- Model: 6.5PAR20DIM/xxxxyyy/SL
- 6.5PAR20DIM/xxxxyyy/B/SL
- 11PAR30DIM/xxxxyyy/SL
- 11PAR30DIM/xxxxyyy/B/SL
- 11PAR30SNDIM/xxxxyyy/SL
- 11PAR30SNDIM/xxxxyyy/B/SL
- 15.5PAR38DIM/xxxxyyy/SL
- 15.5PAR38DIM/xxxxyyy/B/SL

Where xxx means 824-965 which indicates CRI and color temperature
 Where yyy means beam angle



082123

DIMMER COMPATIBILITY

Model: 6.5PAR20DIM/xxxxyyy/SL 6.5PAR20DIM/xxxxyyy/B/SL

Brand	Series	Model	Load (W)	Dimming Range	Dimmability
Lutron	Maestro	MAELV-600	600	0-100%	Compatible
	Skylark Contour	CTELV-303P	300	10-100%	Compatible
	Diva	DVELV-300P	300	0-100%	Compatible
	Nova	NTELV-600	600	20-100%	Compatible
	Caseta	PD-5NE	250	10-100%	Compatible
	Caseta	PD-10NXD	250	10-100%	Compatible
	Diva	DV-600P	600	0-100%	Compatible
	Toggler	TG-600P	600	10-100%	Compatible
	Skylark Contour	CTCL-153P	150	10-100%	Compatible
	Diva	DVCL-153P	150	0-100%	Compatible
Leviton	Maestro C•L	MACL-153M	150	10-100%	Compatible
	Illumatech	IPE04-1LZ	300	20-100%	Compatible
	Sureslide Decora	6674	600	0-100%	Compatible
Cooper	Trimatron	6602	600	0-100%	Compatible
	Aspire	9536	1,000	10-100%	Compatible*

* Minimum 4 lamps



REFINE PAR WITH SWAPPABLE LENS

DIMMER COMPATIBILITY

Model: 11PAR30DIM/xxxxyyyy/SL 11PAR30DIM/xxxxyyyy/B/SL

Brand	Series	Model	Load (W)	Dimming Range	Dimmability
Lutron	Maestro	MAELV-600	600	0-100%	Compatible
	Skylark Contour	CTELV-303P	300	10-100%	Compatible
	Diva	DVELV-300P	300	10-100%	Compatible
	Nova	NTELV-600	600	20-100%	Compatible
	Caseta	PD-5NE	250	10-100%	Compatible
	Caseta	PD-10NXD	250	10-100%	Compatible
	Diva	DV-600P	600	0-100%	Compatible
	Toggler	TG-600P	600	10-100%	Compatible
	Skylark Contour	CTCL-153P	150	0-100%	Compatible
	Diva	DVCL-153P	150	0-100%	Compatible
	Maestro C•L	MACL-153M	150	10-100%	Compatible
Leviton	Illumatech	IPE04-1LZ	300	20-100%	Compatible
	Sureslide Decora	6674	600	0-100%	Compatible
	Trimatron	6602	600	0-100%	Compatible
Cooper	Aspire	9536	1,000	0-100%	Compatible

DIMMER COMPATIBILITY

Model: 11PAR30SNDIM/xxxxyyyy/SL 11PAR30SNDIM/xxxxyyyy/B/SL

Brand	Series	Model	Load (W)	Dimming Range	Dimmability
Lutron	Maestro	MAELV-600	600	0-100%	Compatible
	Skylark Contour	CTELV-303P	300	10-100%	Compatible
	Diva	DVELV-300P	300	10-100%	Compatible
	Nova	NTELV-600	600	20-100%	Compatible
	Caseta	PD-5NE	250	10-100%	Compatible
	Caseta	PD-10NXD	250	10-100%	Compatible
	Diva	DV-600P	600	0-100%	Compatible
	Toggler	TG-600P	600	10-100%	Compatible
	Skylark Contour	CTCL-153P	150	0-100%	Compatible
	Diva	DVCL-153P	150	0-100%	Compatible
	Maestro C•L	MACL-153M	150	10-100%	Compatible
Leviton	Illumatech	IPE04-1LZ	300	20-100%	Compatible
	Sureslide Decora	6674	600	0-100%	Compatible
	Trimatron	6602	600	0-100%	Compatible
Cooper	Aspire	9536	1,000	10-100%	Compatible



REFINE PAR WITH SWAPPABLE LENS

DIMMER COMPATIBILITY

Model: 15.5PAR38DIM/xxxxxyyy/SL 15.5PAR38DIM/xxxxxyyy/B/SL

Brand	Series	Model	Load (W)	Dimming Range	Dimmability
Lutron	Maestro	MAELV-600	600	0-100%	Compatible
	Skylark Contour	CTELV-303P	300	10-100%	Compatible
	Diva	DVELV-300P	300	10-100%	Compatible
	Nova	NTELV-600	600	20-100%	Compatible
	Caseta	PD-5NE	250	10-100%	Compatible
	Caseta	PD-10NXD	250	10-100%	Compatible
	Diva	DV-600P	600	0-100%	Compatible
	Toggle	TG-600P	600	10-100%	Compatible
	Skylark Contour	CTCL-153P	150	10-100%	Compatible
	Diva	DVCL-153P	150	0-100%	Compatible
	Maestro C•L	MACL-153M	150	10-100%	Compatible
Leviton	Illumatech	IPE04-1LZ	300	-	Not Compatible
	Sureslide Decora	6674	600	0-100%	Compatible
	Trimatron	6602	600	0-100%	Compatible
Cooper	Aspire	9536	1,000	10-100%	Compatible**

** Minimum 2 lamps

GREEN CREATIVE has provided this dimmer switch compatibility chart for guidance when selecting a dimmer and lamp combination. Our lamps were tested for compatibility with the above listed dimmers. Dimmers that do not appear on the chart might still be compatible but have not been tested. All testing has been performed with a stable main supply. The quality of the local main, existing installation and wiring, as well as different manufacturer versions of the above dimmers may affect dimming performance. Since no assurance can be provided regarding these factors, it is a general recommendation to perform a test on-site prior to installing the LED lamps.