



**DESCRIPTION**

Providing one-for-one replacement of metal halide or fluorescent fixtures, this LED high bay features rotatable panels that allow you to direct the light output in the direction needed.

**FEATURES**

- Up to 138 LPW ultra-high efficiency delivers superior performance over older HID high bays
- LED panels rotate individually 135-degrees outwards
- Replaces up to a 400W metal halide fixture or a 6 to 8-lamp fluorescent fixture
- 0-10V dimmable from the highest wattage selection only

**LISTINGS**

- UL rated for damp locations
- IP20
- DesignLights Consortium® 5.1 Premium - meets the requirements for the highest DLC qualification for efficacy and lumen maintenance; DLC PN: PLTSN4B1213

**PERFORMANCE**

- CRI: >80
- CCT: 5000K
- LED L70 Life Hours: 50,000
- Philips Lumileds SMD LEDs

**THERMAL**

- -22°F to 122°F (-30°C to 50°C) operating temperature

**ELECTRICAL**

- THD: ≤20%
- Power Factor: ≥0.9
- Input Voltage: 120-277V
- Surge Protection: 6kV
- Dimmable power supply (0-10V)

**INSTALLATION**

- Designed for suspended mounting with V-hooks and 3.28-foot chain included; see installation instructions for more information

**CONSTRUCTION**

- Iron housing with white finish
- Polycarbonate matte lens protects LEDs while evenly distributing light

|                |         |
|----------------|---------|
| Project name   | Type    |
| Catalog number |         |
| Comments       | Voltage |
| Approved by    | Date    |



**WARRANTY**

- 5-year limited warranty; see [pltsolutions.com](http://pltsolutions.com) for warranty details


**APPLICATIONS**

- Warehouses
- Manufacturing Plants
- Distribution Centers
- Grocery Stores
- Gymnasiums
- Indoor Recreational Facilities
- Cold Storage
- Big Box Retail
- Service Repair Centers

## PERFORMANCE SUMMARY

| Item #    | Model  | Watts | Lumens | LPW | CCT   | CRI | Dimming | Voltage  | Replaces | DLC #       | DLC Level   |
|-----------|--------|-------|--------|-----|-------|-----|---------|----------|----------|-------------|-------------|
| PLT-13080 | Linear | 165   | 22,790 | 139 | 5000K | 80  | 0-10V   | 120-277V | MH400    | PLTSN4B1213 | 5.1 Premium |

## DIMENSIONS



### **DIMENSIONS:**

Length: 24.8"

Height: 1.5"

Width: 12.1"

Weight – 6 lbs