DesignLights Consortium





| Model Number | PLTSN1B814[1;2;3]1[1;2;blank][1;2;blank] |
|------------------------|---|
| Classification | Premium |
| Primary Use | High-Bay Luminaires for Commercial and Industrial Buildings |
| Reported Input Wattage | 149.5 W |
| Reported Light Output | 21646 lm |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 81 |
| Product ID | S-13C72T |
| DLC Family Code | SLFALE |
| Listing Status | Listed |
| Date Qualified | 2023-04-04 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting |
|--------------------------------|--|
| Technical Requirements Version | 5.1 |
| Product ID | S-13C72T |
| Manufacturer | Precision Lighting & Transformer, Inc |
| Brand | PLT Solutions |
| Model Number | PLTSN1B814[1;2;3]1[1;2;blank][1;2;blank] |
| Parent | No |
| Classification | Premium |
| DLC Family Code | SLFALE |
| Input Power Type | AC |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Indoor Luminaires |
|-------------------------|---|
| General Application | High-Bay |
| Primary Use Designation | High-Bay Luminaires for Commercial and Industrial Buildings |

CONTROL FEATURES VIEW DETAILS

3/28/24, 10:43 AM

| Integral Controls | Yes | | |
|--|--|--|--|
| Dimming Capability and Range | Continuous Dimming to 10% or below | | |
| Integral Control Capability | No Control Capability | | |
| Sensor Type | Multifunction Sensor, Sensor Receptacle, Daylight Sensing, Occupancy Sensing | | |
| SSL V5 Wired Communication Protocol | 0-10V Analog | | |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol | | |
| Field Adjustable Light Output | No | | |
| White-Tunable | No | | |
| Warm-Dimming | No | | |
| Field Adjustable Light Distribution | Yes | | |
| Field Adjustable Distribution Type | Integral FALD | | |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 21646 lm |
|-------------------------------|-------------|
| Reported Efficacy (AC) | 144.83 lm/W |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 81 |
| Reported R9 | 0 |
| Reported IES Rf | 83 |
| Reported IES Rg | 96 |
| Reported IES Rcs,h1 | -13 |
| Reported Default Light Output | 21646 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 149.5 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 15 % |
| Reported Power Factor | 0.9 |
| Reported Maximum Input Wattage | 149.5 |
| Reported Default Input Wattage | 149.5 W |
| Voltage Range | 120-277 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Field Adjustable Light Distribution Setting Pointing Straight down |
|--|
|--|

VERSION HISTORY VIEW DETAILS

| 2023-04-04 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|
|------------|--------|-----|---------|