DesignLights Consortium





| Model Number | PLTSN1514[1;2;3]2[1;2;blank][1;blank] |
|------------------------|---|
| Classification | Standard |
| Primary Use | High-Bay Luminaires for Commercial and Industrial Buildings |
| Reported Input Wattage | 393.46 W |
| Reported Light Output | 54044.2 lm |
| Reported CCT | 5000 K |
| Reported CRI (Ra) | 84 |
| Product ID | PLNECGHF6Y3J |
| DLC Family Code | EMWAGP |
| Listing Status | Listed |
| Date Qualified | 2021-09-16 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting |
|--------------------------------|---------------------------------------|
| Technical Requirements Version | 5.1 |
| Product ID | PLNECGHF6Y3J |
| Manufacturer | Precision Lighting & Transformer, Inc |
| Brand | PLT |
| Model Number | PLTSN1514[1;2;3]2[1;2;blank][1;blank] |
| Parent | No |
| Classification | Standard |
| DLC Family Code | EMWAGP |
| Input Power Type | AC |
| | |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Indoor Luminaires |
|-------------------------|---|
| General Application | High-Bay |
| Primary Use Designation | High-Bay Luminaires for Commercial and Industrial Buildings |

CONTROL FEATURES VIEW DETAILS

Integral Controls

Yes

3/28/24, 11:08 AM

DLC Qualified Product List - Solid State Lighting

| Dimming Capability and Range | Continuous Dimming to 10% or below |
|--|------------------------------------|
| Integral Control Capability | No Control Capability |
| Sensor Type | Occupancy Sensing |
| SSL V5 Wired Communication Protocol | 0-10V Analog |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol |
| Field Adjustable Light Output | No |
| White-Tunable | No |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | Yes |
| Field Adjustable Distribution Type | Integral FALD |
| | |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| 54044.2 lm |
|-------------|
| 137.36 lm/W |
| 5000 K |
| 84 |
| 10 |
| 85 |
| 95 |
| -12 |
| 54044.2 lm |
| |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 393.46 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 15 % |
| Reported Power Factor | 0.9 |
| Reported Default Input Wattage | 393.46 W |
| Voltage Range | 120-277 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

|--|--|

VERSION HISTORY VIEW DETAILS

| 2021-09-16 Listed 5.1 Standard |
|--------------------------------|
|--------------------------------|