



9W LED A19 60W EQUIV PREMIUM DIMMABLE 3000K E26 120V

Item #774239

Ordering Code LED9A19/P60W/930/J/D/1P

UPC 739698774695

- True shape A19 that closely resembles incandescents and halogens.
- Damp location rated and long-lasting.
- Commonly used in ceiling fixtures and portables.
- Dimmable with a wide range of dimmer types.
- Suitable for fully enclosed fixtures.
- "Complies with the requirements of Appendix JA8 of the Title 24 Part 6 2019 Building Energy Efficiency Standards for Residential and NonResidential Buildings



TECHNICAL SPECIFICATIONS

Item #	Watts	Bulb Type	Base	Volts	Finish/Description	Beam Angle (°)	Color Temperature (CCT)
774239	9	A19	E26	120	Frost	220	3000K
Color	CRI	Lumens	CBCP	Average Hours	M.O.L. (inches)	M.O.D. (inches)	Incandescent Equivalent
Soft White Light	90	800	N/A	25000	4.331	2.362	60
Energy Star	DLC	Title 24 Compliant	Safety Rated	Safety Rating Type	Enclosed Rated	Dimmable	Warranty
Y	N	Y	UL	Damp	Y	Y	5

Order Multiple
QTY
10

APPLICATION SUGGESTIONS



Amusement



Outdoor
Residential



145 West Commercial Ave.
Moonachie, NJ 07074

Dimmer Co

PLEASE NOTE: Compatibility list is based upon testing conducted

Product Family Name:

Item Number:	774238	774239	774240
Ordering Code:	LED9A19/P60W/927/J/D/1P	LED9A19/P60W/930/J/D/1P	LED9A19/P60W/940/J/D/1P
Item Number:			
Ordering Code:			

	Manufacturer	Product	Model Number
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	IllumaTech	IPI06
		SureSlide	6633-P
		Vizia	VPI06-1LZ
	Lutron	Toggler	TG-600
		Lumea	LGCL-600
		Diva	DV-600
		Skylark	S-600
		Maestro	MAW-600
	Legrand	Titan	CD703-PW
		Harmony	D703-PTC
Harmony		H703-PTC	
CFL/LED	Leviton	IllumaTech	IPL06
		Sureslide	6674
		Decora	6672
		Decora Slide	DSL06-1LZ
	Lutron	Skylark	CTCL-153
		Diva	DVCL-153PL
		Maestro	MACL-153MLH
		Skylark	SCL-153P
		Toggler	TGCL-153PH
	Legrand	Radio RA	RA2RR-6CL-PD
Harmony		DCL453-PTC	
Harmony		HCL453PTC	
Electronic Low Voltage	Leviton	Vizia	VPE04
		IllumaTech	IPE04
		Decora	6615-P
	Lutron	Skylark Countour	CTELV-303P
		Diva	DVELV-300P
		Maestro	MAELV-600
		Skylark	SELVB-300P
	Legrand	VIERTI	VTEL-600M-W
Scene Director		SCELV	
Magnetic Low Voltage	Leviton	Vizia	VPM-06
		Decora	6613-P
	Lutron	Maestro	MALV-600
	Legrand	Harmony	DLV703-PW
Titan		CDLV703-PW	
Smart Dimmer	Leviton	Decora Digital (Bluetooth)	DDMX1-BLZ
	Leviton	Decora Smart Z-Wave Technology	DZ6HD
	Leviton	Decora Smart WiFi Technology	DW1KD
	Lutron	Caseta Wireless smart dimmer Wi-Fi	PD-10NXD
	Lutron	Caseta Wireless smart dimmer Wi-Fi	PD-6WCL
	GE	Z WAVE	ZW3005
Universal	Legrand	Adorne SofTap	ADTP703TU
		Miro Decorator	DRD4-W
		Harmony	H703PTUTC
		Adorne Whisper	ADWR700MMTUW2
		Adorne Touch	ADTH700MMTUM2
	Cooper	Decorator	DAL06P-C2-K-L
		Skye	SAL06P-W-K-L

*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.

†May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the

were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating	
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no d
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be
Good	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, dead travel are minor and most of the time not visible. Minor audible noise.
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide di
High End (H.E.) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead tra
Low End (L.E.) Dead Travel	

Contact Information:

Bulbrite Industries Inc.
145 West Commercial Avenue
Moonachie, New Jersey 07074
PHONE: 1-800-528-5555
FAX: 1-800-441-7708
Email: ProductSupport@bulbrite.com
©2017 Bulbrite Industries Inc.
All Rights Reserved.

Compatibility Guide

by the manufacturer in a lab simulated environment. Actual results may vary.

774241

LED9A19/P60W/927/GU24/J/D/1P

774242

LED9A19/P60W/930/GU24/J/D/1P

Lamps per Dimmer

Overall Rating	Recommended Minimum	Maximum Tested*	Notes
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Good	2	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Good	3	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 5%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Good	1	6	Dims down to 15%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Bad	1	6	Dims down to 10%, flicker at HE with 1-6
Good	2	6	Dims down to 1%
Best	1	6	Dims down to 1%
Not Compatible	1	6	Not turn on with 1-6
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 4%
Best	1	6	Dims down to 2%
Best	1	6	Dims down to 2%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 6%
Best	1	6	Dims down to 1%
Good	1	6	dims down to 10%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%
Best	1	6	Dims down to 1%

lights to first turn on if they

dimming range, does not turn off.

is present, dimming not smooth.

which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of

dimming range - can dim down to 10% or less of light output.

level is when the slider can be moved without affecting the light level.