

DesignLights Consortium



Model Number	PLTBO11XX
Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	150.9 W
Reported Light Output	21506 lm
Reported CCT	3000 K
Reported CRI (Ra)	83
Product ID	S-6S9MTH
DLC Family Code	EEEHFN
Listing Status	Listed
Date Qualified	2023-06-27

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-6S9MTH
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTBO11XX
Parent	No
Classification	Premium
DLC Family Code	EEEHFN
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	High-Bay
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Sensor Receptacle,Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	21506 lm
Reported Efficacy (AC)	142.5 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	83
Reported R9	10
Reported IES Rf	83
Reported IES Rg	99
Reported IES Rcs,h1	-11
Reported Minimum Light Output	14254 lm
Reported Maximum Light Output	21506 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	21506 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	150.9 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	100 W
Reported Maximum Input Wattage	150.9
Reported Default Input Wattage	150.9 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2023-06-27	Listed	5.1	Premium
------------	--------	-----	---------