

#### DESCRIPTION

Replace existing 150W metal halide flood fixtures with these more efficient color selectable LED flood fixtures.

#### **FEATURES**

- Delivers up to 144 LPW for highly efficient performance
- Yoke mount adjusts up to 180°
- 0-10V dimming; see Dimmer Compatibility for list of compatible dimmers
- Comes with 11.81" whip
- Light output changes depending on the color temperature selected; see Selectable Table for full breakdown
- Color temperature can be adjusted using the dip switch on the back of the fixture; see installation instructions for more information

#### **LISTINGS**

- · UL rated for wet locations
- IP65
- FCC
- DesignLights Consortium® 5.1 Premium meets the requirements for the highest DLC qualification for efficacy and lumen maintenance; PN - PLTSNH231153

#### PERFORMANCE

CRI: >80

CCT: 3000K, 4000K, 5000K

Rated lifetime L70: 100,000 hours

#### **THERMAL**

• -31°F to 113°F or (-35°C to 45°C) operating temperature

### **ELECTRICAL**

• THD: ≤20%

 Power Factor: ≥0.9 Input Voltage: 120-277V Surge Protection: 2.5kV

Dimmable power supply (0-10V)

#### **INSTALLATION**

 Designed for installation with included yoke mount; see installation instructions for more information.

#### CONSTRUCTION

- Die-cast aluminum housing
- · Durable polyester bronze powder coating withstands demanding environments
- · Clear impact-resistant tempered glass lens

Project name	Туре
Catalog number	
Comments	Voltage
Approved by	Date









#### WARRANTY

· 5-year limited warranty; see pltsolutions.com for warranty details

#### **APPLICATIONS**

- · Safety and Security Lighting
- Sign Lighting
- Building Facades

## **PERFORMANCE SUMMARY**

Item #	Watts*	CCT*	Beam Angle	CRI	Dimming	Voltage	Replaces	Mounting	BUG	DLC #	DLC Level
PLT-13124	35W	3000/ 4000/ 5000	145°	>80	0-10V	120-277V	150W MH	Yoke Mount	B2-U0-G0	PLTSNH231153	5.1 Premium

<sup>\*</sup> See Selectable Table for full breakdown

### **SELECTABLE TABLE**

Wattage	сст	Lumen	Efficacy	
35	3000K	4642	133	
	4000K	5034	144	
	5000K	4864	139	

## **DIMMER COMPATIBILITY**

Brand	Model		
Leviton	SD710		
Leviton	IP710		
Legrand	RH4FBL3PW		
Lutron	NFTV		
Lutron	NTSTV		
Lutron	DVTV		

## **DIMENSIONS**



# **DIMENSIONS:**

Length - 5.79"

Yoke Length - 7.95"

Length (with mount) - 7.24"

Yoke Width - 4.92"

Width - 7.95"

Yoke Height - 1.10"

Depth - 2.60"

Weight - 2.34 lbs

Weight (w/ mount) - 2.87 lbs

### **PHOTOMETRICS**

