

# DesignLights Consortium



Model Number	PLTSN4B62[1;2]3[1;2;3;4;5;blank]
Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	109.1 W
Reported Light Output	14829 lm
Reported CCT	5000 K
Reported CRI (Ra)	83
Product ID	S-84CK9D
DLC Family Code	<a href="#">SLFAFV</a>
Listing Status	Listed
Date Qualified	2022-11-30

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-84CK9D
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT Solutions
Model Number	PLTSN4B62[1;2]3[1;2;3;4;5;blank]
Parent	No
Classification	Premium
DLC Family Code	SLFAFV
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	High-Bay
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings

## CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Multifunction Sensor, Daylight Sensing, Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	14829 lm
Reported Efficacy (AC)	135.92 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	83
Reported R9	8
Reported IES Rf	84
Reported IES Rg	95
Reported IES Rcs,h1	-12
Reported Default Light Output	14829 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	109.1 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Default Input Wattage	109.1 W
Voltage Range	120-277 V

## VERSION HISTORY VIEW DETAILS

2022-11-30	Listed	5.1	Premium
------------	--------	-----	---------