

Color Selectable LED Flood Light Fixture

PLT-13132

DESCRIPTION

Replace existing metal halide flood fixtures with these more efficient color selectable LED flood fixtures.

FEATURES

- Delivers up to 135 LPW for highly efficient performance
- Slipfitter adjusts up to 180° (90° left and 90° right)
- Silver-face reflector is perfect for aesthetic landscape lighting
- 0-10V dimming; see Dimmer Compatibility for list of compatible dimmers
- Light output changes depending on the color temperature selected; see Selectable Table for full breakdown
- Color temperature can be adjusted using the dip switch on the back of the fixture; see installation instructions for more information

LISTINGS

- · UL rated for wet locations
- IP65
- FCC

PERFORMANCE

- CRI: >80
- CCT: 3000K, 4000K, 5000K
- Rated lifetime L70: 100,000 hours

THERMAL

• -22°F to 113°F or (-30°C to 45°C) operating temperature

ELECTRICAL

- THD: ≤20%
- Power Factor: ≥0.9
- Input Voltage: 120-277V
- Surge Protection: 4Kv
- Dimmable power supply (0-10V)

INSTALLATION

• Designed for installation with included mount; see Performance Summary for a full breakdown of which mount is included. For information on how to install these fixtures, see installation instructions.

CONSTRUCTION

- · Die-cast aluminum housing
- Durable polyester bronze powder coating withstands demanding environments
- · Impact-resistant tempered glass lens and silver reflector

Туре	
Voltage	
Date	
	Voltage







WARRANTY

 5-year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Safety and Security Lighting
- Sign Lighting
- Building Facades
- Landscape Lighting

PERFORMANCE SUMMARY

Item #	Watts*	CCT*	Beam Angle	CRI	Dimming	Voltage	Replaces	Mounting	BUG
PLTS-12316	105W	3000/ 4000/ 5000	145°	>80	0-10V	120-277V	250W MH	Slipfitter	B4-U0-G1

*See Selectable Table for full breakdown

SELECTABLE TABLE

Wattage	сст	Lumen	Efficacy
105	3000K	13,243	126
	4000K	14,129	135
	5000K	13,616	130


DIMMER COMATIBILITY

Brand	Model
Leviton	SD710
Leviton	IP710
Legrand	RH4FBL3PW
Lutron	NFTV
Lutron	NTSTV
Lutron	DVTV

DIMENSIONS



PHOTOMETRICS



DIMENSIONS

Length – 9.09" Length (with mount) – 15.94" Width – 11.42" Depth – 3.5" Weight – 7.2 lbs Weight w/ mount – 8.82 lbs Slipfitter Length – 6.93" Splifitter Width – 4.88" Slipfitter Height – 2.87"