# **DesignLights Consortium**





Model Number	PLTM445142
Classification	Standard
Primary Use	Direct Linear Ambient Luminaires
Reported Input Wattage	54 W
Reported Light Output	6372 lm
Reported CCT	3500 K
Reported CRI (Ra)	82
Product ID	PR4U6KCO
DLC Family Code	EEEGKI
Listing Status	Listed
Date Qualified	2021-09-03

#### **PRODUCT INFORMATION VIEW DETAILS**

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PR4U6KCO
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTM445142
Parent	Yes
Classification	Standard
DLC Family Code	EEEGKI
Length	4.0 ft
Input Power Type	AC

### **PRODUCT CATEGORIZATION VIEW DETAILS**

Category	Indoor Luminaires
General Application	Linear Ambient
Primary Use Designation	Direct Linear Ambient Luminaires

### **CONTROL FEATURES VIEW DETAILS**

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	6372 lm
Reported Efficacy (AC)	118 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	82
Reported R9	14
Reported IES Rf	80
Reported IES Rg	90
Reported IES Rcs,h1	-12
Reported Minimum Light Output	4318 lm
Reported Maximum Light Output	6480 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	6372 lm

### REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	54 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	34 W
Reported Maximum Input Wattage	54
Reported Default Input Wattage	54 W
Voltage Range	120-277 V

#### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Tested Voltage for Minimum Efficacy	120
-------------------------------------	-----

Tested Light Output	6395.92 lm
Tested Efficacy (AC)	119.44 lm/W
Tested CCT	3553 K
Tested CRI (Ra)	84
Tested R9	13
Tested IES Rf	84
Tested IES Rg	94
Tested IES Rcs,h1	-12 %
Tested Duv	-0.0017

## **TESTED ELECTRICAL PERFORMANCE VIEW DETAILS**

Tested Input Wattage	53.55 W
Tested Total Harmonic Distortion	16.55 %
Tested Power Factor	0.9178

### **VERSION HISTORY VIEW DETAILS**

2021-09-03	Listed	5.1	Standard