DesignLights Consortium





| Model Number | PLTSN521X1[2;3][1;2;3;4;5;Blank][1;Blank] |
|------------------------|--|
| Classification | Premium |
| Primary Use | Outdoor Full-Cutoff Wall-Mounted Area Luminaires |
| Reported Input Wattage | 57.69 W |
| Reported Light Output | 7270.1 lm |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 70 |
| Product ID | PLOFK905S145 |
| DLC Family Code | <u>EMWADJ</u> |
| Listing Status | Listed |
| Date Qualified | 2021-06-15 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting | | |
|--------------------------------|---|--|--|
| Technical Requirements Version | 5.1 | | |
| Product ID | PLOFK905S145 | | |
| Manufacturer | Precision Lighting & Transformer, Inc | | |
| Brand | PLT | | |
| Model Number | PLTSN521X1[2;3][1;2;3;4;5;Blank][1;Blank] | | |
| Parent | No | | |
| Classification | Premium | | |
| DLC Family Code | EMWADJ | | |
| Input Power Type | AC | | |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Outdoor Luminaires | |
|-------------------------|--|--|
| General Application | Mid Output | |
| Primary Use Designation | Outdoor Full-Cutoff Wall-Mounted Area Luminaires | |

CONTROL FEATURES VIEW DETAILS

| Integral Controls | Yes | | |
|--|--------------------------------------|--|--|
| Dimming Capability and Range | Continuous Dimming to 10% or below | | |
| Sensor Type | Occupancy Sensor, Exterior Photocell | | |
| SSL V5 Wired Communication Protocol | 0-10V Analog | | |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol | | |
| Field Adjustable Light Output | Yes | | |
| White-Tunable | Yes | | |
| Warm-Dimming | No | | |
| Field Adjustable Light Distribution | No | | |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 7270.1 lm |
|-------------------------------|-------------|
| Reported Efficacy (AC) | 126.02 lm/W |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 70 |
| Reported R9 | -30 |
| Reported IES Rf | 73 |
| Reported IES Rg | 96 |
| Reported IES Rcs,h1 | -16 |
| Reported Minimum Light Output | 1890.3 lm |
| Reported Maximum Light Output | 7270.1 lm |
| Reported Minimum CCT | 3000 K |
| Reported Maximum CCT | 5000 K |
| Reported Default Light Output | 7270.1 lm |
| Reported BUG Rating | B3 U3 G1 |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 57.69 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 15 % |
| Reported Power Factor | 0.9 |
| Reported Minimum Input Wattage | 15 W |
| Reported Maximum Input Wattage | 57.69 |
| Reported Default Input Wattage | 57.69 W |
| Voltage Range | 120-277 V |

VERSION HISTORY VIEW DETAILS

| 2021-06-15 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|
|------------|--------|-----|---------|