plano (ARCH **LCDL** | Solstice LED COMMERCIAL DOWNLIGHT Superior Performance Year After Year



LCDL | Solstice

Built to last. Reliable Solution.



DURABLE ALUMINUM SHELL

LCDL Solstice downlight feature a durable, high quality aluminum shell with frosted PC diffuser.



EASY INSTALLATION

The Solstice includes spring-action housing clips and translucent end caps & joiner plate accessory for seamless installation of continuous linear runs.



0-10V DIMMING

Supports tri-mode dimmability from 10% to 100% in TRIAC, ELV and 0-10V



5-Year Warranty



50,000 Hours



Black



Nickel



Trim Options (sold separately)

High CRI

SELECTAD

SELECTABL

Suitable for use in wet locations

Easy install with

Spring-Loaded Clips

Suitable for use in -4°F to 113°F

Available in 4 Sizes

4" | 6" | 8" | 10"

WATTselect Options Up to 52W

CCTselect Options

2700 | 3000 | 3500 | 4000 | 5000

Efficacy up to 110lm/W

Ordering Guide

Model Series	Size (in)	3-WATTselect (W)	5-CCTselect	EM Driver
LCDL Commercial Downlights	4 4in 6 6in 8 8in 10 10in	(4in) -0612 6W/9W/12W (6in) -1222 12W/17W/22W (8in) -1730 17W/24W/30W (8in) -3252 32W/42W/52W (10in) -2238 22W/30W/38W	CS I CCTselect: 2700K / 3000K / 3500K / 4000K / 5000K /	EM15 EM15-HMB/170
Note: Default settings are displayed in GRAY.	. Spec selections and optiona	I accessories are displayed in RED.		
Ordering number example:	Choose your	model specifications:		

LCD10-2238CS Please place dashes (-) in correct order. LCDL

Model Series

10

Size



-2238

Watt

((1)),





CS

CCTselect





EM15

EM Driver







