

DesignLights Consortium



Model Number	PLTM5C1111
Classification	Standard
Primary Use	1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	40 W
Reported Light Output	4400 lm
Reported CCT	3500 K
Reported CRI (Ra)	81
Product ID	S-PD9J79
DLC Family Code	SLFAYU
Listing Status	Listed
Date Qualified	2024-02-27

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-PD9J79
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTM5C1111
Parent	Yes
Classification	Standard
DLC Family Code	SLFAYU
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer
Primary Use Designation	1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	No
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4400 lm
Reported Efficacy (AC)	110 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	81
Reported R9	6
Reported IES Rf	82
Reported IES Rg	98
Reported IES Rcs,h1	-12
Reported Minimum Light Output	3000 lm
Reported Maximum Light Output	4400 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	4400 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	40 W
Reported Total Harmonic Distortion	10.1 %
Reported Power Factor	0.964
Reported Minimum Input Wattage	25 W
Reported Maximum Input Wattage	40
Reported Default Input Wattage	40 W
Voltage Range	120-277

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
Tested Light Output	4567 lm

Tested Efficacy (AC)	107.53 lm/W
Tested CCT	3445 K
Tested CRI (Ra)	81
Tested R9	6
Tested IES Rf	82
Tested IES Rg	98
Tested IES Rcs,h1	-12 %
Tested Duv	-0.0018

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	42.5 W
Tested Total Harmonic Distortion	14.3 %
Tested Power Factor	0.923

VERSION HISTORY VIEW DETAILS

2024-02-27	Listed	5.1	Standard
------------	--------	-----	----------